

Package ‘AdMit’

August 20, 2009

Version 1-01.03

Date 2009-06-12

Title Adaptive Mixture of Student-t distributions

Author David Ardia, Lennart F. Hoogerheide and Herman K. van Dijk

Maintainer David Ardia <david.ardia@unifr.ch>

Depends mvtnorm

Suggests coda

Description This package provides functions to perform the fitting of an adaptive mixture of Student-t distributions to a target density through its kernel function. The mixture approximation can then be used as the importance density in importance sampling or as the candidate density in the Metropolis-Hastings algorithm to obtain quantities of interest for the target density itself.

License GPL (>= 2)

URL <http://perso.unifr.ch/david.ardia/>

Repository CRAN

Date/Publication 2009-08-20 13:47:40

R topics documented:

AdMit	2
AdMitIS	7
AdMitMH	10
Mit	13
Index	16

Description

Function which performs the fitting of an adaptive mixture of Student-t distributions to approximate a target density through its kernel function

Usage

```
AdMit(KERNEL, mu0, Sigma0 = NULL, control = list(), ...)
```

Arguments

KERNEL	kernel function of the target density on which the adaptive mixture is fitted. This function should be vectorized for speed purposes (i.e., its first argument should be a matrix and its output a vector). Moreover, the function must contain the logical argument <code>log</code> . If <code>log = TRUE</code> , the function returns (natural) logarithm values of the kernel function. NA and NaN values are not allowed. (See <i>*Details*</i> for examples of KERNEL implementation.)
mu0	initial value in the first stage optimization (for the location of the first Student-t component) in the adaptive mixture, or location of the first Student-t component if <code>Sigma0</code> is not NULL.
Sigma0	scale matrix of the first Student-t component (square, symmetric and positive definite). Default: <code>Sigma0 = NULL</code> , i.e., the scale matrix of the first Student-t component is estimated by the function <code>AdMit</code> .
control	control parameters (see <i>*Details*</i>).
...	further arguments to be passed to KERNEL.

Details

The argument `KERNEL` is the kernel function of the target density, and it should be vectorized for speed purposes.

As a first example, consider the kernel function proposed by Gelman-Meng (1991):

$$k(x_1, x_2) = \exp\left(-\frac{1}{2}[Ax_1^2x_2^2 + x_1^2 + x_2^2 - 2Bx_1x_2 - 2C_1x_1 - 2C_2x_2]\right)$$

where commonly used values are $A = 1$, $B = 0$, $C_1 = 3$ and $C_2 = 3$.

A vectorized implementation of this function might be:

```
GelmanMeng <- function(x, A = 1, B = 0, C1 = 3, C2 = 3, log = TRUE)
{
  if (is.vector(x))
    x <- matrix(x, nrow = 1)
  r <- -.5 * (A * x[,1]^2 * x[,2]^2 + x[,1]^2 + x[,2]^2
```

```

- 2 * B * x[,1] * x[,2] - 2 * C1 * x[,1] - 2 * C2 * x[,2])
if (!log)
  r <- exp(r)
as.vector(r)
}

```

This way, we may supply a point (x_1, x_2) for \mathbf{x} and the function will output a single value (i.e., the kernel estimated at this point). But the function is vectorized, in the sense that we may supply a $(N \times 2)$ matrix of values for \mathbf{x} , where rows of \mathbf{x} are points (x_1, x_2) and the output will be a vector of length N , containing the kernel values for these points. Since the `AdMit` procedure evaluates `KERNEL` for a large number of points, a vectorized implementation is important. Note also the additional argument `log = TRUE` which is used for numerical stability.

As a second example, consider the following (simple) econometric model:

$$y_t \sim i.i.d. N(\mu, \sigma^2) \quad t = 1, \dots, T$$

where μ is the mean value and σ is the standard deviation. Our purpose is to estimate $\theta = (\mu, \sigma)$ within a Bayesian framework, based on a vector y of T observations; the kernel thus consists of the product of the prior and the likelihood function. As previously mentioned, the kernel function should be vectorized, i.e., treat a $(N \times 2)$ matrix of points θ for which the kernel will be evaluated. Using the common (Jeffreys) prior $p(\theta) = \frac{1}{\sigma}$ for $\sigma > 0$, a vectorized implementation of the kernel function might be:

```

KERNEL <- function(theta, y, log = TRUE)
{
  if (is.vector(theta))
    theta <- matrix(theta, nrow = 1)

  ## sub function which returns the log-kernel for a given
  ## thetai value (i.e., a given row of theta)
  KERNEL_sub <- function(thetai)
  {
    if (thetai[2] > 0) ## check if sigma>0
    { ## if yes, compute the log-kernel at thetai
      r <- - log(thetai[2])
        + sum(dnorm(y, thetai[1], thetai[2], TRUE))
    }
    else
    { ## if no, returns -Infinity
      r <- -Inf
    }
    as.numeric(r)
  }

  ## 'apply' on the rows of theta (faster than a for loop)
  r <- apply(theta, 1, KERNEL_sub)
  if (!log)
    r <- exp(r)
  as.numeric(r)
}

```

Since this kernel function also depends on the vector y , it must be passed to `KERNEL` in the `AdMit` function. This is achieved via the argument `...`, i.e., `AdMit(KERNEL, mu = c(0, 1), y = y)`.

To gain even more speed, implementation of `KERNEL` might rely on C or Fortran code using the functions `.C` and `.Fortran`. An example is provided in the file `'AdMitJSS.R'` in the package's folder.

The argument `control` is a list that can supply any of the following components:

- Ns** number of draws used in the evaluation of the importance sampling weights (integer number not smaller than 100). Default: `Ns = 1e5`.
- Np** number of draws used in the optimization of the mixing probabilities (integer number not smaller than 100 and not larger than `Ns`). Default: `Np = 1e3`.
- Hmax** maximum number of Student-t components in the adaptive mixture (integer number not smaller than one). Default: `Hmax = 10`.
- df** degrees of freedom parameter of the Student-t components (real number not smaller than one). Default: `df = 1`.
- CVtol** tolerance for the relative change of the coefficient of variation (real number in $[0,1]$). The adaptive algorithm stops if the new component leads to a relative change in the coefficient of variation that is smaller or equal than `CVtol`. Default: `CVtol = 0.1`, i.e., 10%.
- weightNC** weight assigned to the new Student-t component of the adaptive mixture as a starting value in the optimization of the mixing probabilities (real number in $[0,1]$). Default: `weightNC = 0.1`, i.e., 10%.
- trace** tracing information on the adaptive fitting procedure (logical). Default: `trace = FALSE`, i.e., no tracing information.
- IS** should importance sampling be used to estimate the mode and the scale matrix of the Student-t components (logical). Default: `IS = FALSE`, i.e., use numerical optimization instead.
- ISpercent** vector of percentage(s) of largest weights used to estimate the mode and the scale matrix of the Student-t components of the adaptive mixture by importance sampling (real number(s) in $[0,1]$). Default: `ISpercent = c(0.05, 0.15, 0.3)`, i.e., 5%, 15% and 30%.
- ISscale** vector of scaling factor(s) used to rescale the scale matrix of the mixture components (real positive numbers). Default: `ISscale = c(1, 0.25, 4)`.
- trace.mu** Tracing information on the progress in the optimization of the mode of the mixture components (non-negative integer number). Higher values may produce more tracing information (see the source code of the function `optim` for further details). Default: `trace.mu = 0`, i.e., no tracing information.
- maxit.mu** maximum number of iterations used in the optimization of the modes of the mixture components (positive integer). Default: `maxit.mu = 500`.
- reltol.mu** relative convergence tolerance used in the optimization of the modes of the mixture components (real number in $[0,1]$). Default: `reltol.mu = 1e-8`.
- trace.p, maxit.p, reltol.p** the same as for the arguments above, but for the optimization of the mixing probabilities of the mixture components.

Value

A list with the following components:

`CV`: vector (of length H) of coefficients of variation of the importance sampling weights.

`mit`: list (of length 4) containing information on the fitted mixture of Student-t distributions, with the following components:

`p`: vector (of length H) of mixing probabilities. `mu`: matrix (of size $H \times d$) containing the vectors of modes (in row) of the mixture components. `Sigma`: matrix (of size $H \times d^2$) containing the scale matrices (in row) of the mixture components. `df`: degrees of freedom parameter of the Student-t components.

where $H(\geq 1)$ is the number of components in the adaptive mixture of Student-t distributions and $d(\geq 1)$ is the dimension of the first argument in `KERNEL`.

`summary`: data frame containing information on the optimization procedures. It returns for each component of the adaptive mixture of Student-t distribution: 1. the method used to estimate the mode and the scale matrix of the Student-t component ('USER' if `Sigma0` is provided by the user; numerical optimization: 'BFGS', 'Nelder-Mead'; importance sampling: 'IS', with percentage(s) of importance weights used and scaling factor(s)); 2. the time required for this optimization; 3. the method used to estimate the mixing probabilities ('NLMINB', 'BFGS', 'Nelder-Mead', 'NONE'); 4. the time required for this optimization; 5. the coefficient of variation of the importance sampling weights.

Note

Further details and examples of the R package `AdMit` can be found in Ardia, Hoogerheide, van Dijk (2009a,b). See also the package vignette by typing `vignette("AdMit")` and the files 'AdMitJSS.txt' and 'AdMitRnews.txt' in the '/doc' package's folder.

Further details on the core algorithm are given in Hoogerheide (2006), Hoogerheide, Kaashoek, van Dijk (2007) and Hoogerheide, van Dijk (2008).

The adaptive mixture `mit` returned by the function `AdMit` is used by the function `AdMitIS` to perform importance sampling using `mit` as the importance density or by the function `AdMitMH` to perform independence chain Metropolis-Hastings sampling using `mit` as the candidate density.

Please cite the package in publications. Use `citation("AdMit")`.

Author(s)

David Ardia <david.ardia@unifr.ch> for the R port, Lennart F. Hoogerheide and Herman K. van Dijk for the `AdMit` algorithm.

References

Ardia, D., Hoogerheide, L.F., van Dijk, H.K. (2009a). `AdMit`: Adaptive Mixture of Student-t Distributions. *The R Journal* **1**(1), pp.25–30. <http://journal.r-project.org/2009-1/>

Ardia, D., Hoogerheide, L.F., van Dijk, H.K. (2009b). Adaptive Mixture of Student-t Distributions as a Flexible Candidate Distribution for Efficient Simulation: The R Package AdMit. *Journal of Statistical Software* **29**(3), pp.1–32. <http://www.jstatsoft.org/v29/i03/>

Gelman, A., Meng, X.-L. (1991). A Note on Bivariate Distributions That Are Conditionally Normal. *The American Statistician* **45**(2), pp.125–126.

Hoogerheide, L.F. (2006). *Essays on Neural Network Sampling Methods and Instrumental Variables*. PhD thesis, Tinbergen Institute, Erasmus University Rotterdam (NL). ISBN: 9051708261. (Book nr. 379 of the Tinbergen Institute Research Series.)

Hoogerheide, L.F., Kaashoek, J.F., van Dijk, H.K. (2007). On the Shape of Posterior Densities and Credible Sets in Instrumental Variable Regression Models with Reduced Rank: An Application of Flexible Sampling Methods using Neural Networks. *Journal of Econometrics* **139**(1), pp.154–180. doi: 10.1016/j.jeconom.2006.06.009.

Hoogerheide, L.F., van Dijk, H.K. (2008). Possibly Ill-Behaved Posteriors in Econometric Models: On the Connection between Model Structures, Non-elliptical Credible Sets and Neural Network Simulation Techniques. *Tinbergen Institute discussion paper* **2008-036/4**. <http://www.tinbergen.nl/discussionpapers/08036.pdf>

See Also

[AdMitIS](#) for importance sampling using an adaptive mixture of Student-t distributions as the importance density, [AdMitMH](#) for the independence chain Metropolis-Hastings algorithm using an adaptive mixture of Student-t distributions as the candidate density.

Examples

```
## Gelman and Meng (1991) kernel function
GelmanMeng <- function(x, A = 1, B = 0, C1 = 3, C2 = 3, log = TRUE)
{
  if (is.vector(x))
    x <- matrix(x, nrow = 1)
  r <- -.5 * (A * x[,1]^2 * x[,2]^2 + x[,1]^2 + x[,2]^2
             - 2 * B * x[,1] * x[,2] - 2 * C1 * x[,1] - 2 * C2 * x[,2])
  if (!log)
    r <- exp(r)
  as.vector(r)
}

## Run AdMit (with default values)
set.seed(1234)
outAdMit <- AdMit(GelmanMeng, mu0 = c(0.0, 0.1))
print(outAdMit)

## Run AdMit (using importance sampling to estimate
## the modes and the scale matrices)
set.seed(1234)
outAdMit <- AdMit(KERNEL = GelmanMeng,
                  mu0 = c(0.0, 0.1),
                  control = list(IS = TRUE))
print(outAdMit)
```

```

## Simple econometric model:  $y_t \sim \text{i.i.d. } N(\mu, \sigma^2)$ 
## Jeffreys prior  $p(\theta) \propto 1/\sigma$  for  $\sigma > 0$ 
KERNEL <- function(theta, y, log = TRUE)
{
  if (is.vector(theta))
    theta <- matrix(theta, nrow = 1)

  KERNEL_sub <- function(thetai)
  {
    if (thetai[2] > 0)
      {
        r <- - log(thetai[2]) + sum(dnorm(y, thetai[1], thetai[2], TRUE))
      }
    else
      {
        r <- -Inf
      }
    as.numeric(r)
  }
  r <- apply(theta, 1, KERNEL_sub)
  if (!log)
    r <- exp(r)
  as.numeric(r)
}

## Generate 20 draws for  $\mu = 1$  and  $\sigma = 0.5$ 
set.seed(1234)
y <- rnorm(20, 2, 0.5)

## Run AdMit (with default values); pass the vector y
## of observations using the ... argument of AdMit and
## print steps of the fitting process
outAdMit <- AdMit(KERNEL = KERNEL,
                  mu0 = c(1.0, 1.0),
                  y = y, control = list(trace = TRUE))
print(outAdMit)

```

AdMitIS

Importance Sampling using an Adaptive Mixture of Student-t Distributions as the Importance Density

Description

Performs importance sampling using an adaptive mixture of Student-t distributions as the importance density

Usage

```
AdMitIS(N = 1e5, KERNEL, G = function(theta){theta}, mit = list(), ...)
```

Arguments

N	number of draws used in importance sampling (positive integer number). Default: $N = 1e5$.
KERNEL	kernel function of the target density on which the adaptive mixture of Student-t distributions is fitted. This function should be vectorized for speed purposes (i.e., its first argument should be a matrix and its output a vector). Moreover, the function must contain the logical argument <code>log</code> . If <code>log = TRUE</code> , the function returns (natural) logarithm values of the kernel function. NA and NaN values are not allowed. (See the function <code>AdMit</code> for examples of <code>KERNEL</code> implementation.)
G	function of interest used in importance sampling (see <i>*Details*</i>).
mit	list containing information on the mixture approximation (see <i>*Details*</i>).
...	further arguments to be passed to <code>KERNEL</code> and/or <code>G</code> .

Details

The `AdMitIS` function estimates $E_p[g(\theta)]$, where p is the target density, g is an (integrable w.r.t. p) function and E denotes the expectation operator, by importance sampling using an adaptive mixture of Student-t distributions as the importance density.

By default, the function `G` is given by:

```
G <- function(theta)
{
  theta
}
```

and therefore, `AdMitIS` estimates the mean of `theta` by importance sampling. For other definitions of `G`, see **Examples**.

The argument `mit` is a list containing information on the mixture approximation. The following components must be provided:

p vector (of length H) of mixing probabilities.

mu matrix (of size $H \times d$) containing the vectors of modes (in row) of the mixture components.

Sigma matrix (of size $H \times d^2$) containing the scale matrices (in row) of the mixture components.

df degrees of freedom parameter of the Student-t components (real number not smaller than one).

where $H(\geq 1)$ is the number of components of the adaptive mixture of Student-t distributions and $d(\geq 1)$ is the dimension of the first argument in `KERNEL`. Typically, `mit` is estimated by the function `AdMit`.

Value

A list with the following components:

`ghat`: a vector containing the importance sampling estimates. `NSE`: a vector containing the numerical standard error of the components of `ghat`. `RNE`: a vector containing the relative numerical efficiency of the components of `ghat`.

Note

Further details and examples of the R package AdMit can be found in Ardia, Hoogerheide, van Dijk (2009a,b). See also the package vignette by typing `vignette("AdMit")` and the files ‘AdMitJSS.txt’ and ‘AdMitRnews.txt’ in the ‘/doc’ package’s folder.

Further information on importance sampling can be found in Geweke (1989) or Koop (2003).

Please cite the package in publications. Use `citation("AdMit")`.

Author(s)

David Ardia <david.ardias@unifr.ch>

References

Ardia, D., Hoogerheide, L.F., van Dijk, H.K. (2009a). AdMit: Adaptive Mixture of Student-t Distributions. *The R Journal* **1**(1), pp.25–30. <http://journal.r-project.org/2009-1/>

Ardia, D., Hoogerheide, L.F., van Dijk, H.K. (2009b). Adaptive Mixture of Student-t Distributions as a Flexible Candidate Distribution for Efficient Simulation: The R Package AdMit. *Journal of Statistical Software* **29**(3), pp.1–32. <http://www.jstatsoft.org/v29/i03/>

Geweke, J.F. (1989). Bayesian Inference in Econometric Models Using Monte Carlo Integration. *Econometrica* **57**(6), pp.1317–1339.

Koop, G. (2003). *Bayesian Econometrics*. Wiley-Interscience (London, UK). ISBN: 0470845678.

See Also

[AdMit](#) for fitting an adaptive mixture of Student-t distributions to a target density through its KERNEL function, [AdMitMH](#) for the independence chain Metropolis-Hastings algorithm using an adaptive mixture of Student-t distributions as the candidate density.

Examples

```
## Gelman and Meng (1991) kernel function
GelmanMeng <- function(x, A = 1, B = 0, C1 = 3, C2 = 3, log = TRUE)
{
  if (is.vector(x))
    x <- matrix(x, nrow = 1)
  r <- -.5 * (A * x[,1]^2 * x[,2]^2 + x[,1]^2 + x[,2]^2
             - 2 * B * x[,1] * x[,2] - 2 * C1 * x[,1] - 2 * C2 * x[,2])
  if (!log)
    r <- exp(r)
  as.vector(r)
}

## Run the AdMit function to fit the mixture approximation
set.seed(1234)
outAdMit <- AdMit(KERNEL = GelmanMeng,
                 mu0 = c(0.0, 0.1))

## Use importance sampling with the mixture approximation as the
## importance density
```

```

outAdMitIS <- AdMitIS(KERNEL = GelmanMeng, mit = outAdMit$mit)
print(outAdMitIS)

## Covariance matrix estimated by importance sampling
G.cov <- function(theta, mu)
{
  G.cov_sub <- function(x)
    (x - mu)

  theta <- as.matrix(theta)
  tmp <- apply(theta, 1, G.cov_sub)
  if (length(mu) > 1)
    t(tmp)
  else
    as.matrix(tmp)
}

outAdMitIS <- AdMitIS(KERNEL = GelmanMeng,
                      G = G.cov,
                      mit = outAdMit$mit,
                      mu = c(1.459, 1.459))

print(outAdMitIS)

## Covariance matrix
V <- matrix(outAdMitIS$ghat, 2, 2)
print(V)

## Correlation matrix
cov2cor(V)

```

AdMitMH

Independence Chain Metropolis-Hastings Algorithm using an Adaptive Mixture of Student-t Distributions as the Candidate Density

Description

Performs independence chain Metropolis-Hastings (M-H) sampling using an adaptive mixture of Student-t distributions as the candidate density

Usage

```
AdMitMH(N = 1e5, KERNEL, mit = list(), ...)
```

Arguments

N number of draws generated by the independence chain M-H algorithm (positive integer number). Default: $N = 1e5$.

KERNEL	kernel function of the target density on which the adaptive mixture is fitted. This function should be vectorized for speed purposes (i.e., its first argument should be a matrix and its output a vector). Moreover, the function must contain the logical argument <code>log</code> . If <code>log = TRUE</code> , the function returns (natural) logarithm values of kernel function. NA and NaN values are not allowed. (See the function <code>AdMit</code> for examples of <code>KERNEL</code> implementation.)
mit	list containing information on the mixture approximation (see <code>*Details*</code>).
...	further arguments to be passed to <code>KERNEL</code> .

Details

The argument `mit` is a list containing information on the adaptive mixture of Student-t distributions. The following components must be provided:

p vector (of length H) of mixing probabilities.

mu matrix (of size $H \times d$) containing the vectors of modes (in row) of the mixture components.

Sigma matrix (of size $H \times d^2$) containing the scale matrices (in row) of the mixture components.

df degrees of freedom parameter of the Student-t components (real number not smaller than one).

where $H(\geq 1)$ is the number of components and $d(\geq 1)$ is the dimension of the first argument in `KERNEL`. Typically, `mit` is estimated by the function `AdMit`.

Value

A list with the following components:

`draws`: matrix (of size $N \times d$) of draws generated by the independence chain M-H algorithm, where $N(\geq 1)$ is the number of draws and $d(\geq 1)$ is the dimension of the first argument in `KERNEL`.

`accept`: acceptance rate of the independence chain M-H algorithm.

Note

Further details and examples of the R package `AdMit` can be found in Ardia, Hoogerheide and van Dijk (2009a,b). See also the package vignette by typing `vignette("AdMit")` and the files `'AdMitJSS.txt'` and `'AdMitRnews.txt'` in the `'/doc'` package's folder.

Further information on the Metropolis-Hastings algorithm can be found in Chib and Greenberg (1995) and Koop (2003).

Please cite the package in publications. Use `citation("AdMit")`.

Author(s)

David Ardia <(david.ardia@unifr.ch)>

References

- Ardia, D., Hoogerheide, L.F., van Dijk, H.K. (2009a). AdMit: Adaptive Mixture of Student-t Distributions. *The R Journal* **1**(1), pp.25–30. <http://journal.r-project.org/2009-1/>
- Ardia, D., Hoogerheide, L.F., van Dijk, H.K. (2009b). Adaptive Mixture of Student-t Distributions as a Flexible Candidate Distribution for Efficient Simulation: The R Package AdMit. *Journal of Statistical Software* **29**(3), pp.1–32. <http://www.jstatsoft.org/v29/i03/>
- Chib, S., Greenberg, E. (1995). Understanding the Metropolis-Hasting Algorithm. *The American Statistician* **49**(4), pp.327–335.
- Koop, G. (2003). *Bayesian Econometrics*. Wiley-Interscience (London, UK). ISBN: 0470845678.

See Also

[AdMitIS](#) for importance sampling using an adaptive mixture of Student-t distributions as the importance density, [AdMit](#) for fitting an adaptive mixture of Student-t distributions to a target density through its KERNEL function; the package coda for MCMC output analysis.

Examples

```
## Gelman and Meng (1991) kernel function
GelmanMeng <- function(x, A = 1, B = 0, C1 = 3, C2 = 3, log = TRUE)
{
  if (is.vector(x))
    x <- matrix(x, nrow = 1)
  r <- -.5 * (A * x[,1]^2 * x[,2]^2 + x[,1]^2 + x[,2]^2
             - 2 * B * x[,1] * x[,2] - 2 * C1 * x[,1] - 2 * C2 * x[,2])
  if (!log)
    r <- exp(r)
  as.vector(r)
}

## Run the AdMit function to fit the mixture approximation
set.seed(1234)
outAdMit <- AdMit(KERNEL = GelmanMeng,
                  mu0 = c(0.0, 0.1))

## Run M-H using the mixture approximation as the candidate density
outAdMitMH <- AdMitMH(KERNEL = GelmanMeng, mit = outAdMit$mit)
options(digits = 4, max.print = 40)
print(outAdMitMH)

## Use functions provided by the package coda to obtain
## quantities of interest for the density whose kernel is 'GelmanMeng'
library("coda")
draws <- as.mcmc(outAdMitMH$draws)
draws <- window(draws, start = 1001)
colnames(draws) <- c("X1", "X2")
summary(draws)
summary(draws)$stat[,3]^2 / summary(draws)$stat[,4]^2 ## RNE
plot(draws)
```

Mit

*Mixture of Student-t Distributions***Description**

Density function or random generation for an adaptive mixture of Student-t distributions

Usage

```
dMit(theta, mit = list(), log = TRUE)
rMit(N = 1, mit = list())
```

Arguments

<code>theta</code>	matrix (of size $N \times d$, where $N, d \geq 1$) of real values.
<code>mit</code>	list containing information on the mixture approximation (see *Details*).
<code>log</code>	logical; if <code>log = TRUE</code> , returns (natural) logarithm values of the density. Default: <code>log = TRUE</code> .
<code>N</code>	number of draws (positive integer number).

Details

`dMit` returns the density values while `rMit` generates draws from a mixture of Student-t distributions.

The argument `mit` is a list containing information on the adaptive mixture of Student-t distributions. The following components must be provided:

- p** vector (of length H) of mixture probabilities.
- mu** matrix (of size $H \times d$) containing the vectors of modes (in row) of the mixture components.
- Sigma** matrix (of size $H \times d^2$) containing the scale matrices (in row) of the mixture components.
- df** degrees of freedom parameter of the Student-t components (integer number not smaller than one).

where $H(\geq 1)$ is the number of components and $d(\geq 1)$ is the dimension of the mixture approximation. Typically, `mit` is estimated by the function `AdMit`. If the `mit = list()`, a Student-t distribution located at `rep(0, d)` with scale matrix `diag(d)` and one degree of freedom parameter is used.

Value

Vector (of length N of density values, or matrix (of size $N \times d$) of random draws, where $d(\geq 1)$ is the dimension of the mixture approximation.

Note

Further details and examples of the R package AdMit can be found in Ardia, Hoogerheide, van Dijk (2009a,b). See also the package vignette by typing `vignette("AdMit")` and the files ‘AdMitJSS.txt’ and ‘AdMitRnews.txt’ in the ‘/doc’ package’s folder.

Please cite the package in publications. Use `citation("AdMit")`.

Author(s)

David Ardia <david.ardia@unifr.ch>

References

Ardia, D., Hoogerheide, L.F., van Dijk, H.K. (2009a). AdMit: Adaptive Mixture of Student-t Distributions. *The R Journal* **1**(1), pp.25–30. <http://journal.r-project.org/2009-1/>

Ardia, D., Hoogerheide, L.F., van Dijk, H.K. (2009b). Adaptive Mixture of Student-t Distributions as a Flexible Candidate Distribution for Efficient Simulation: The R Package AdMit. *Journal of Statistical Software* **29**(3), pp.1–32. <http://www.jstatsoft.org/v29/i03/>

See Also

[AdMit](#) for fitting an adaptive mixture of Student-t distributions to a given function `KERNEL`, [AdMitIS](#) for importance sampling using an adaptive mixture of Student-t distributions as the importance density, [AdMitMH](#) for the independence chain Metropolis-Hastings using an adaptive mixture of Student-t distributions as the candidate density.

Examples

```
## One dimensional two components mixture of Student-t distributions
mit <- list(p = c(0.5, 0.5),
           mu = matrix(c(-2.0, 0.5), 2, 1, byrow = TRUE),
           Sigma = matrix(0.1, 2),
           df = 10)

## Generate draws from the mixture
hist(rMit(10000, mit = mit), nclass = 100, freq = FALSE)
x <- seq(from = -5.0, to = 5.0, by = 0.01)
## Add the density to the histogram
lines(x, dMit(x, mit = mit, log = FALSE), col = "red", lwd = 2)

## Two dimensional (one component mixture) Student-t distribution
mit <- list(p = 1,
           mu = matrix(0.0, 1.0, 2.0),
           Sigma = matrix(c(1.0, 0.0, 0.0, 1.0), 1, 4),
           df = 10)

## Function used to plot the mixture in two dimensions
dMitPlot <- function(x1, x2, mit = mit)
{
  dMit(cbind(x1, x2), mit = mit, log = FALSE)
}
x1 <- x2 <- seq(from = -10.0, to = 10.0, by = 0.1)
thexlim <- theylim <- range(x1)
```

```
z <- outer(x1, x2, FUN = dMitPlot, mit = mit)
## Contour plot of the mixture
contour(x1, x2, z, nlevel = 20, las = 1,
        col = rainbow(20),
        xlim = thexlim, ylim = theyylim)
par(new = TRUE)
## Generate draws from the mixture
plot(rMit(10000, mit = mit), pch = 20, cex = 0.3,
     xlim = thexlim, ylim = theyylim, col = "red", las = 1)

## Two dimensional three components mixture of Student-t distributions
mit <- list(p = c(0.2, 0.3, 0.5),
           mu = matrix(c(-5.0, -1.0, -3.0, 5.0, 1.0, 2.0), 3, 2, byrow = TRUE),
           Sigma = matrix(.5 * c(1.0, 1.0, 1.0, 0.0, 0.0, 0.0,
                                0.0, 0.0, 0.0, 1.0, 1.0, 1.0), 3, 4),
           df = 10)
x1 <- x2 <- seq(from = -10.0, to = 10.0, by = 0.1)
thexlim <- theyylim <- range(x1)
z <- outer(x1, x2, FUN = dMitPlot, mit = mit)
## Contour plot of the mixture
contour(x1, x2, z, nlevel = 20, las = 1, col = rainbow(20),
        xlim = thexlim, ylim = theyylim)
par(new = TRUE)
## Generate random draws from the mixture
plot(rMit(10000, mit = mit), pch = 20, cex = 0.3, xlim = thexlim,
     ylim = theyylim, col = "red", las = 1)
```

Index

*Topic **distribution**

Mit, [13](#)

*Topic **htest**

AdMit, [2](#)

AdMitIS, [7](#)

AdMitMH, [10](#)

AdMit, [2](#), [8](#), [9](#), [11–14](#)

AdMitIS, [5](#), [6](#), [7](#), [12](#), [14](#)

AdMitMH, [5](#), [6](#), [9](#), [10](#), [14](#)

dMit (*Mit*), [13](#)

Mit, [13](#)

optim, [4](#)

rMit (*Mit*), [13](#)