

Package ‘FactoClass’

July 21, 2009

Version 1.0.1

Date 2009-07-21

Title Combination of Factorial Methods and Cluster Analysis

Author Campo Elias Pardo <cepardot@unal.edu.co> and Pedro Cesar del Campo <pcdelcampon@unal.edu.co>, with the contributions from Ivan Diaz <ildiazm@unal.edu.co>, Mauricio Sadinle <msadinleg@unal.edu.co>.

Maintainer Campo Elias Pardo <cepardot@unal.edu.co>

Depends R (>= 2.7.0), ade4, xtable

Description Multivariate exploration of a data table with factorial analysis and cluster methods.

License GPL (>= 2)

Encoding latin1

Repository CRAN

Date/Publication 2009-07-21 16:14:03

R topics documented:

Bogota	2
BreedsDogs	2
centroids	3
cluster.carac	4
ColorAdjective	5
dudi.tex	6
Fac.Num	7
FactoClass	8
FactoClass.tex	10
kmeansW	12
list.to.data	13
planfac	14
plotFactoClass	16

stableclus	17
Vietnam	18
ward.cluster	19

Index	21
--------------	-----------

Bogota	<i>Localities by Stratum in Bogota City</i>
--------	---

Description

Contingency Table that indicates the number of blocks of Bogota, in localities by stratum (DAPD 1997, p.77).

Usage

`data(Bogota)`

Format

Object whit class `data.frame` of 19 rows and 7 columns.

Source

DAPD (1997), Population, stratification and socioeconomic aspects of Bogota

References

C.E. Pardo y J.E. Ortiz (2004). Analisis multivariado de datos en R. Simposio de Estadística, Cartagena Colombia. <http://www.docentes.unal.edu.co/cepardot/analmultir.pdf>

BreedsDogs	<i>Breeds of Dog</i>
------------	----------------------

Description

Table that describes 27 breeds of dog considering their size, weight, speed, intelligence, affectivity, aggressiveness and function.

Usage

`data(BreedsDogs)`

Format

Object of class `data.frame` with 27 rows and 7 columns with the following description:

	VARIABLE	CATEGORIES		
[,1]	Size(SIZE)	Small(sma)	Mediun(med)	Large(lar)
[,2]	Weight(WEIG)	lightweight(lig)	Mediun(med)	Heavy(hea)
[,3]	Speed(SPEE)	Low(low)	Mediun(med)	High(hig)
[,4]	Intelligence(INTE)	Low(low)	Mediun(med)	High(hig)
[,5]	Affectivity(AFFE)	Low(low)	High(hig)	
[,6]	aggressiveness(AGGR)	Low(low)	High(hig)	
[,7]	function(FUNC)	Company(com)	Hunt(hun)	Utility(uti)

Source

Fine, J. (1996), 'Iniciacion a los analisis de datos multidimensionales a partir de ejemplos', Notas de clase, Montevideo.

References

Brefort, A.(1982), 'Letude des races canines a partir de leurs caracteristiques qualitatives', HEC - Jouy en Josas

centroids

Centroids of the Classes of a Partition

Description

It evaluates the centroids of a partition with the weights in `rw`

Usage

```
centroids(df, cl, rw=rep(1/nrow(df), nrow(df)))
```

Arguments

<code>df</code>	object of class <code>data.frame</code> , with the data of variables or coordinates
<code>cl</code>	vector indicating the cluster of each element
<code>rw</code>	weight of the rows of <code>df</code> , by default the same

Value

Object of class `list` with the following:

<code>centroids</code>	class <code>centroids</code>
<code>weights</code>	class <code>weights</code>

Author(s)

Campo Elias Pardo (cepardot@unal.edu.co)

Examples

```
data(iris)
centroids(iris[, -5], iris[, 5])
```

cluster.carac

Cluster Characterization by Variables.

Description

It makes the characterization of the classes or cluster considering the variables in tabla. These variables can be quantitative, qualitative or frequencies.

Usage

```
cluster.carac( tabla , clase , tipo.v="d" , v.lim = 2 )
```

Arguments

tabla	object data.frame with variables of characterization, the variables must be of a single type (quantitative, qualitative or frequencies)
clase	vector that determines the partition of the table
tipo.v	type of variables: quantitative("continuas"), qualitative ("nominales") or frequencies("frecuencia")
v.lim	test value to show the variable or category like characteristic.

Details

For nominal or frequency variables it compares the percentage of the categories within each class with the global percentage. For continuous variables it compares the average within each class with the general average. Categories and variables are ordered within each class by the test values and it shows only those that pass the threshold v.lim.

Value

Object of class list. It has the characterization of each class or cluster.

Author(s)

Pedro Cesar del Campo (pcdelcampon@unal.edu.co), Campo Elias Pardo (cepardot@unal.edu.co), Mauricio Sadinle (msadinleg@unal.edu.co)

References

Lebart, L. and Morineau, A. and Piron, M. (1995) Statistique exploratoire multidimensionnelle, Paris.

Examples

```
data(BreedsDogs)
BD.act <- BreedsDogs[-7] # active variables
BD.function <- subset(BreedsDogs,select=7)
cluster.carac(BD.act,BD.function,"ca",2.0) # nominal variables

data(iris)
iris.act <- Fac.Num(iris)$numeric
clase <- Fac.Num(iris)$factor
cluster.carac(iris.act,clase,"co",2.0) # continuous variables

# frequency variables
data(BreedsDogs)
attach(BreedsDogs)
weig<-table(FUNC,WEIG)
weig<-data.frame(weig[,1],weig[,2],weig[,3])
cluster.carac(weig, row.names(weig), "fr", 2) # frequency variables
detach(BreedsDogs)
```

ColorAdjective *Associations between colors and adjectives.*

Description

A group of students from Nanterre University (Paris X) were presented with a list of eleven colours: blue, yellow, red, white, pink, brown, purple, grey, black, green and orange. Each person in the group was asked to describe each color with one or more adjectives. A final list of 89 adjectives were associated with eleven colors.

Usage

```
data(ColorAdjective)
```

Format

Object of class data.frame with 89 rows and 11 columns.

Source

Jambu, M. and Lebeaux M.O. Cluster Analysis and Data Analysis. North-Holland. Amsterdam 1983.

References

Fine, J. (1996), 'Iniciacion a los analisis de datos multidimensionales a partir de ejemplos', Notas de curso, Montevideo.

dudi.tex	<i>LaTeX Tables of Coordinates and Aids to Interpretation of Principal Axis Methods</i>
----------	---

Description

Coordinates and aids of interpretation are wrote in tabular environment of LaTeX inside a Table

Usage

```
dudi.tex(dudi, job="", aidsC=TRUE, aidsR=TRUE, append=TRUE)
latex(obj, job="latex", tit="", lab="", append=TRUE, dec=1)
```

Arguments

dudi	an object of class dudi
job	a name to identify files and outputs
aidsC	if it is TRUE the coordinates and aids of interpretation of the columns are printed
aidsR	if it is TRUE the coordinates and aids of interpretation of the rows are printed
append	if it is TRUE LaTeX outputs are appended on the file
...	
obj	object to export to LaTeX
tit	title of the table
lab	label for crossed references of LaTeX table
dec	number of decimal digits

Details

latex function is used to builp up a table. The aids of interpretation are obtained with `inertia.dudi` of `ade4`. A file is wrote in the work directory (`job.txt`) with the following tables:

tvalp eigenvalues

c1 eigenvectors

co column coordinates

col.abs column contributions in percentage

col.rel quality of the representation of columns in percentage

col.cum accumulated quality of the representation of columns in percentage/100

li row coordinates

row.abs row contributions in percent

row.rel quality of the representation of rows in percentage

row.cum accumulated quality of the representation of rows in percentage/100

Author(s)

Campo Elías PARDO <cepardot@unal.edu.co>

Examples

```
data(ardeche)
coal <- dudi.coa(ardeche$tab, scann = FALSE, nf = 4)
dudi.tex(coal, job="Ardeche")
```

Fac.Num

Division of qualitative and quantitative variables.

Description

An object of class `data.frame` is divided into a list with two tables, one with quantitative variables and the other with qualitative variables.

Usage

```
Fac.Num(tabla)
```

Arguments

`tabla` object of class 'data.frame'

Value

It returns one list with one or two objects of class `data.frame` with the following characteristics:

`factor` table with the qualitative variables
`numeric` table with the quantitative variables

Author(s)

Pedro Cesar Del Campo <pcdelcampon@unal.edu.co>

Examples

```
data(BreedsDogs)
Fac.Num(BreedsDogs)

data(iris)
Fac.Num(iris)
```

FactoClass

*Combination of Factorial Methods and Cluster Analysis***Description**

Performs the factorial analysis of the data and a cluster analysis using the `nfcl` first factorial coordinates

Usage

```
FactoClass( dfact, metodo, dfilu = NULL , nf = 2, nfcl = 10, k.clust = 3,
            scanFC = TRUE , n.max = 5000 , n.clus = 1000 , sign = 2.0,
            conso=TRUE , n.indi = 25 )

## S3 method for class 'FactoClass':
print(x, ...)

analysis.clus(X,W)
```

Arguments

<code>dfact</code>	object of class <code>data.frame</code> , with the data of active variables.
<code>metodo</code>	function of <code>ade4</code> for <code>ade4</code> factorial analysis, <code>dudi.pca</code> , Principal Component Analysis; <code>dudi.coa</code> , Correspondence Analysis; <code>witwit.coa</code> , Internal Correspondence Analysis; <code>dudi.acm</code> , Multiple Correspondence Analysis ...
<code>dfilu</code>	illustrative variables (default <code>NULL</code>)
<code>nf</code>	number of axes to use into the factorial analysis (default 2)
<code>nfcl</code>	number of axes to use in the classification (default 10)
<code>k.clust</code>	number of classes to work (default 3)
<code>scanFC</code>	if is <code>TRUE</code> , it asks in the console the values <code>nf</code> , <code>nfcl</code> y <code>k.clust</code>
<code>n.max</code>	when <code>rowname(dfact) >= n.max</code> , k-means is performed previous to hierarchical clustering (default 5000)
<code>n.clus</code>	when <code>rowname(fact) >= n.max</code> , the previous k-means is performed with <i>n.clus</i> groups (default 1000)
<code>sign</code>	threshold test value to show the characteristic variables and modalities
<code>conso</code>	when <code>conso</code> is <code>TRUE</code> , the process of consolidating the classification is performed (default <code>TRUE</code>)
<code>n.indi</code>	number of indices to draw in the histogram (default 25)
<code>...</code>	
<code>x</code>	object of class <code>FactoClass</code>
<code>X</code>	coordinates of the elements of a class
<code>W</code>	weights of the elements of a class

Details

Lebart et al. (1995) present a strategy to analyze a data table using multivariate methods, consisting of an initial factorial analysis according to the nature of the compiled data, followed by the performance of mixed clustering. The mixed clustering combines hierarchical clustering using the Ward's method with K-means clustering. Finally a partition of the data set and the characterization of each one of the classes is obtained, according to the active and illustrative variables, being quantitative, qualitative or frequency.

FactoClass is a function that connects procedures of the package `ade4` to perform the analysis factorial of the data and from `stats` for the cluster analysis.

The function `analysis.clus` calculates the geometric characteristics of each class: size, inertia, weight and square distance to the origin.

For impression in LaTeX format see [FactoClass.tex](#)

To draw factorial planes with cluster see [plotFactoClass](#)

Value

object of class `FactoClass` with the following:

<code>dudi</code>	object of class <code>dudi</code> from <code>ade4</code> with the specifications of the factorial analysis
<code>nfcl</code>	number of axes selected for the classification
<code>k</code>	number of classes
<code>indices</code>	table of indices obtained through WARD method
<code>cor.clus</code>	coordinates of the clusters
<code>clus.summ</code>	summary of the clusters
<code>cluster</code>	vector indicating the cluster of each element
<code>carac.cate</code>	cluster characterization by qualitative variables
<code>carac.cont</code>	cluster characterization by quantitative variables
<code>carac.frec</code>	cluster characterization by frequency active variables

Author(s)

Pedro Cesar del Campo (pcdelcampon@unal.edu.co), Campo Elias Pardo (cepardot@unal.edu.co) <http://www.docentes.unal.edu.co/cepardot>, Ivan Diaz (ildiazm@unal.edu.co), Mauricio Sadinle (msadinleg@unal.edu.co)

References

Lebart, L. and Morineau, A. and Piron, M. (1995) *Statistique exploratoire multidimensionnelle*, Paris.

Examples

```

# Cluster analysis with Correspondence Analysis
data(ColorAdjective)
FC.col <-FactoClass(ColorAdjective, dudi.coa)
6
10
5

FC.col

FC.col$dudi

# Cluster analysis with Multiple Correspondence Analysis
data(BreedsDogs)

BD.act <- BreedsDogs[-7] # active variables
BD.ilu <- BreedsDogs[7]  # ilustrative variables

FC.bd <-FactoClass( BD.act, dudi.acm, k.clust = 4,
                  scanFC = FALSE, dfilu = BD.ilu, nfcl = 10)

FC.bd

FC.bd$clus.summ
FC.bd$indices

```

FactoClass.tex *Table of Coordinates, Aids of Interpretation of the Principal Axes and Cluster Analysis in LaTeX format.*

Description

The coordinates, aids of interpretation and results of cluster analysis of an object of class `FactoClass` are written in tables for edition in LaTeX format and written in a file.

Usage

```

FactoClass.tex(FC, job="", append=TRUE, dir = getwd(), p.clust = FALSE )

## S3 method for class 'FactoClass.tex':
print(x, ...)

latexDF(obj, job="latex" ,tit="" ,lab="" , append=TRUE ,dec=1,
        dir = getwd() , to.print = TRUE )
roundDF(tabla,dec=1)

```

Arguments

FC	object of class <code>FactoClass</code> .
job	A name to identify the exit.
append	if is 'TRUE' the exit in LaTeX format is added to the file.
dir	name of the directory in which the file is kept.
p.clust	the value of this parameter is 'TRUE' or 'FALSE' to print or not the cluster of each element.
tabla	object of class 'data frame'.
dec	number of decimal.
x	object of class <code>FactoClass.tex</code>
obj	object of class <code>data.frame</code> .
tit	title of the table in LaTeX format.
lab	label of the table in LaTeX format.
to.print	if it is 'TRUE' the table is also printed in the console.
...	

Details

This function helps with the construction of tables in *LaTeX* format. Besides, it allows a easy reading of the generated results by `FactoClass`. The function `latexDF` is an entrance to `xtable` and turns an object of class `data.frame` a table in LaTeX format.

Value

object of class `FactoClass.tex` with the following characteristics:

tvalp	eigenvalues * 1000.
c1	eigenvectors.
co	coordinates of the columns.
col.abs	contribution of each column to the inertia of the axis (percentage).
col.rel	quality of representation of each column (percentage).
col.cum	quality of representation of each column accumulated in the subspace (percentage).
li	coordinates of the rows.
row.abs	contribution of each rows to the inertia of the axis (percentage).
row.rel	quality of representation of each rows (percentage).
row.cum	quality of representation of each rows accumulated in the subspace (percentage).
indices	table of indices of level generated by the Ward cluster analysis.
cor.clus	coordinates of the center of gravity of each cluster.
clus.summ	summary of the cluster.
carac.cate	cluster characterization by qualitative variables.
carac.cont	cluster characterization by quantitative variables.
cluster	vector indicating the cluster of each element.

Author(s)

Pedro Cesar del Campo (pcdelcampon@unal.edu.co), Campo Elias Pardo (cepardot@unal.edu.co)

Examples

```
data(BreedsDogs)

BD.act <- BreedsDogs[-7] # active variables
BD.ilu <- BreedsDogs[7]  # illustrative variables

# MCA

FaCl <- FactoClass( BD.act, dudi.acm,
                   scanFC = FALSE, dfilu = BD.ilu, nfcl = 10, k.clust = 4 )

FactoClass.tex(FaCl, job="BreedsDogs1", append=TRUE)
FactoClass.tex(FaCl, job="BreedsDogs",  append=TRUE , p.clust = TRUE)
```

kmeansW

K-means with Weights of the Elements

Description

It is a modification of kmeans Hartigan-Wong algorithm to consider the weight of the elements to classify.

Usage

```
kmeansW(x, centers, weight = rep(1/nrow(x), nrow(x)),
        iter.max = 10, nstart = 1)
```

Arguments

x	A numeric vector, matrix or data frame.
centers	Either the number of clusters or a set of initial (distinct) cluster centres. If a number, a random set of (distinct) rows in x is chosen as the initial centres.
weight	weight of the elements of x. by default the same.
iter.max	The maximum number of iterations allowed.
nstart	If centers is a number, how many random sets should be chosen?

Details

With the 'Hartigan-Wong' algorithm, this function performs the *K-means* clustering diminishing inertia intra classes.

Value

object of class `FactoClass.tex` with the following characteristics:

`cluster` vector indicating the cluster of each element.

...

Author(s)

Pedro Cesar del Campo (pcdelcampon@unal.edu.co), Campo Elias Pardo (cepardot@unal.edu.co),
Mauricio Sadinle (msadinleg@unal.edu.co) <http://www.docentes.unal.edu.co/cepardot>

Examples

```
data(Bogota)
ac.bog <- Bogota[-1]
il.bog <- Bogota[ 1]

acs <- dudi.coa( ac.bog, nf=6 , scannf = FALSE )

kmeansW( acs$li, 7, acs$lw )
```

<code>list.to.data</code>	<i>list to data.frame</i>
---------------------------	---------------------------

Description

Modification of an object of class `list` into an object of class `data.frame`.

Usage

```
list.to.data(lista, nvar="clasif")
```

Arguments

`lista` `list` that contains several `data.frame` of the same structure.
`nvar` (Optional) Name of the new variable that considers the partition given by the elements of the list.

Details

This function turns an object of class `list` into an object of class `data.frame`, this function is used internally to create objects of class `data.frame` to make tables in *LaTeX* format.

Value

Object of class `data.frame`.

Author(s)

Pedro Cesar Del Campo (pcdelcampon@unal.edu.co)

Examples

```
A <- data.frame(r1=rnorm(5), r2=rnorm(5))
B <- data.frame(r1=rnorm(15), r2=rnorm(15))

LL <- list(A=A, B=B)
LL
list.to.data(LL)
```

planfac

Correspondence Analysis Factorial Planes

Description

It plots factorial planes of a correspondence analysis

Usage

```
planfac(dudi, x=1, y=2, xlim=NULL, ylim=NULL, rotx=FALSE, roty=FALSE, roweti=row.names(dudi),
        coleti=row.names(dudi$co), titre=NULL, axislabel=TRUE,
        col.row="black", col.col="blue", cex=0.8, cex.row=0.8, cex.col=0.8,
        all.point=TRUE, Trow=TRUE, Tcol=TRUE, cframe=1.2, ucal=0,
        cex.global=1, infaxes="out")
sutil.grid(cgrid, scale=TRUE)
```

Arguments

dudi	object of type dudi
x	number indentifying the factor to be used as horizontal axis. Default x=1
y	number indentifying the factor to be used as vertical axis. Default y=2
xlim	the x limits (x1, x2) of the plot
ylim	the y limits of the plot
rotx	TRUE if you want change the sign of the horizontal coordinates. Default FALSE
roty	TRUE if you want change the sign of the vertical coordinates. Default FALSE
roweti	selected row points for the graphic. Default all points
coleti	selected column points for the graphic. Default all points
titre	graphic title
axislabel	if it is TRUE the axis information is written
col.row	color for row points and row labels. Default "black"

<code>col.col</code>	color for column points and column labels. Default "blue"
<code>cex</code>	global scale for the labels. Default <code>cex=0.8</code>
<code>cex.row</code>	scale for row points and row labels. Default <code>cex.row=0.8</code>
<code>cex.col</code>	scale for column points and column labels. Default <code>cex.col=0.8</code>
<code>all.point</code>	If it is TRUE, all points are outlined. Default <code>all.point=TRUE</code>
<code>Trow</code>	if it is TRUE the row points are outlined. Default TRUE
<code>Tcol</code>	if it is TRUE the column points are outlined. Default TRUE
<code>cframe</code>	scale for graphic limits
<code>ucal</code>	quality representation threshold (percentage) in the plane . Default <code>ucal=0</code>
<code>cex.global</code>	scale for the label sizes
<code>infaxes</code>	place to put the axes information: "out","in","no". Default <code>infaxes="out"</code> . If <code>infaxes="out"</code> the graphic is similar to FactoMineR graphics, otherwise the style is similar to the one in ade4, without axes information when <code>infaxes="no"</code>
<code>...</code>	
<code>cgrid</code>	
<code>scale</code>	

Details

Plot the selected factorial plane. `sutil.grid` is used by `planfac`

Value

It graphs the factorial plane x,y using `co,li` of a "dudi" "coa" object. If `ucal > 0`, the function `inertia.dudi` is used to calculate the quality of representation on the plane

Author(s)

Campo Elias Pardo (cepardot@unal.edu.co)

<http://www.docentes.unal.edu.co/cepardot>

Examples

```
data(ardeche)
ca <- dudi.coa(ardeche$tab, scannf=FALSE, nf=4)
# FactoMineR style
planfac(ca, ucal=40, all.point=FALSE, titre="SCA of Ardeche, First Factorial Plane")
dev.new()
# ade4 style
planfac(ca, x=3, y=4, ucal=20, all.point=FALSE, infaxes="in", titre="SCA of
Ardeche, Plane 3-4")
```

plotFactoClass *Factorial Planes Showing the Classes*

Description

For objects of class FactoClass it graphs a factorial plane showing the center of gravity of the cluster, and identifying with colors the cluster to which each element belongs.

Usage

```
plotFactoClass(FC , x=1, y=2,xlim=NULL,ylim=NULL, rotx=FALSE, roty=FALSE,
               roweti=row.names(dudi$li),
               coleti=row.names(dudi$co),titre=NULL, axislabel=TRUE,
               col.row=1:FC$k, col.col="blue", cex=0.8, cex.row=0.8, cex.col=0.8,
               all.point=TRUE, Trow=TRUE, Tcol=TRUE,
               cframe=1.2, ucal=0,
               cex.global=1, infaxes="out",nclus=paste("cl", 1:FC$k, sep=""),cex.c
```

Arguments

FC	object of class FactoClass .
x	number indentifying the factor to be used as horizontal axis. Default x=1
y	number indentifying the factor to be used as vertical axis. Default y=2
xlim	the x limits (x1, x2) of the plot
ylim	the y limits of the plot
rotx	TRUE if you want change the sign of the horizontal coordinates (default FALSE).
roty	TRUE if you want change the sign of the vertical coordinates (default FALSE).
roweti	selected row points for the graphic. Default all points.
coleti	selected column points for the graphic. Default all points.
titre	graphics title.
axislabel	if it is TRUE the axis information is written.
col.row	color for row points and row labels. Default 1:FC\$k.
col.col	color for row points and row labels. Default "grey55".
cex	global scale for the labels. Default cex=0.8.
cex.row	scale for row points and row labels. Default cex.row=0.8.
cex.col	scale for column points and column labels. Default cex.col=0.8.
cex.clu	scale for cluster points and cluster labels. (default cex.row).
all.point	if if is TRUE, all points are outlined. Default all.point=TRUE.
Trow	if it is TRUE the row points are outlined. Default TRUE.
Tcol	if it is TRUE the column points are outlined. Default TRUE.

nclus	labels for the clusters (default c11, c12, ...)
cframe	scale for graphics limits
ucal	quality Representation Threshold in the plane. Default ucal=0
cex.global	scale for the label sizes
infaxes	place to put the axes information: "out","in","no". Default infaxes="out". If infaxes="out" the graphic is similar to FactoMineR graphics, otherwise the style is similar to the one in ade4, without axes information when infaxes="no"
cstar	length of the rays between the centroids of the classes and their points

Details

It draws the factorial plane with the clusters. Only for objects `FactoClass` see [FactoClass](#). The factorial plane is drawn with `planfac` and the classes are projected with `s.class` of `ade4`

Value

It draws the factorial plane `x, y` using `co,li` of the object of class `FactoClass`. If `ucal > 0`, the function `inertia.dudi` is used to calculate the quality of representation in the plane.

Author(s)

Campo Elías Pardo (cepardot@unal.edu.co) Pedro Cesar del Campo (pcdelcampon@unal.edu.co),

Examples

```
data(Bogota)
Bog.act <- Bogota[-1]
Bog.ilu <- Bogota[ 1]

FC.Bogota<-FactoClass(Bog.act, dudi.coa,Bog.ilu,nf=2,nfcl=5,k.clust=5,scanFC=FALSE)

plotFactoClass(FC.Bogota,titre="Primer plano factorial del ACS de la TC de manzanas de Bogota",
  col.row=c("maroon2","orchid4","darkgoldenrod2","dark red","aquamarine4"))
```

stableclus

Stable Clusters from K-means

Description

It performs stable clusters from several partitions from K-means changing the initial points. It uses the coordinates of an previous principal axes method

Usage

```
stableclus(dudi,part=2,k.clust=2,ff.clus=NULL,bplot=TRUE,kmns=FALSE)
```

Arguments

dudi	object of type dudi
part	the number of partitions to obtain
k.clust	the number of clusters each partition
ff.clus	the number of ended clusters, if is NULL (default), it asks in the console the values ff.clus
bplot	if is TRUE, the barplot of the stable clusters is plotted
kmns	when hmns=TRUE, a kmeansW is performed with argument centers equal to the centroids of the stable classes retained

Details

Lebart, L. and Morineau, A. and Piron, M. (1995) Statistique exploratoire multidimensionnelle, Paris.

Value

list with:	
class	vector indicating the cluster of each element
stacl	vector containing the stable clusters in descending order

Author(s)

Carlos Andres Arias <caariasr@unal.edu.co>, Campo Elias Pardo <cepardot@unal.edu.co>, Diana Carolina Zarate <dczarated@unal.edu.co>

Examples

```
data(BreedsDogs)
acm <- dudi.acm(BreedsDogs[, -7], scannf = FALSE, nf=10)
stableclus(acm, 2, 3, 4)
```

 Vietnam

Student opinions about the Vietnam War

Description

The newspaper of the students of the University of Chapel Hill (North Carolina) conducted a survey of student opinions about the Vietnam War in May 1967. Responses were classified by sex, year in the program and one of four opinions:

- A** defeat power of North Vietnam by widespread bombing and land invasion
- B** follow the present policy
- C** withdraw troops to strong points and open negotiations on elections involving the Viet Cong
- D** immediate withdrawal of all U.S. troops

Usage

```
data (Vietnam)
```

Format

The 3147 consulted students were classified considering the sex, year of study and chosen strategy, originating a contingency table of 10 rows: M1 to M5 and F1 to F5 (the years of education are from 1 to 5 and sexes are male (M) and female (F)) and 4 columns A, B, C and D.

Source

Fine, J. (1996), 'Iniciación a los análisis de datos multidimensionales a partir de ejemplos', Notes of course, Montevideo

References

Julian Faraway (2007). faraway: Functions and datasets for books by Julian Faraway, R package version 1.0.2, <http://www.maths.bath.ac.uk/>

ward.cluster	<i>Hierarchic Classification by Ward's Method</i>
--------------	---

Description

Performs the classification by Ward's method from the matrix of Euclidean distances.

Usage

```
ward.cluster(dista, peso = NULL , plots = TRUE, h.clust = 2, n.indi = 25 )
```

Arguments

dista	matrix of Euclidean distances (<code>class(dista)=="dist"</code>).
peso	(Optional) weight of the individuals, by default equal weights
plots	it makes dendrogram and histogram of the Ward's method
h.clust	if it is '0' returns a object of class <code>hclust</code> and a table of level indices, if it is '1' returns a object of class <code>hclust</code> , if it is '2' returns a table of level indices.
n.indi	number of indices to draw in the histogram (default 25).

Details

It is an entrance to the function `h.clus` to obtain the results of the procedure presented in Lebart et al. (1995). Initially the matrix of distances of Ward of the elements to classify is calculated:

The Ward's distance between two elements to classify i and l is given by:

$$W(i, l) = (m_i * m_l) / (m_i + m_l) * dist(i, l)^2$$

where m_i y m_l are the weights and $dist(i, l)$ is the Euclidean distance between them.

Value

It returns an object of class `hclust` and a table of level indices (depending of `h.clust`). If `plots = TRUE` it draws the indices of level and the dendrogram.

Author(s)

Pedro Cesar del Campo (pcdelcampon@unal.edu.co), Campo Elias Pardo (cepardot@unal.edu.co)
<http://www.docentes.unal.edu.co/cepardot>

References

Lebart, L. and Morineau, A. and Piron, M. (1995) Statistique exploratoire multidimensionnelle, Paris.

Examples

```
data(ardeche)
ca <- dudi.coa(ardeche$stab, scannf=FALSE, nf=4)

ward.cluster( dista= dist(ca$li), peso=ca$lw )

dev.new()
HW <- ward.cluster( dista= dist(ca$li), peso=ca$lw ,h.clust = 1)
plot(HW)
rect.hclust(HW, k=4, border="red")
```

Index

*Topic **cluster**

FactoClass, 7
plotFactoClass, 16

*Topic **datasets**

Bogota, 1
BreedsDogs, 2
ColorAdjective, 5
Vietnam, 18

*Topic **hplot**

cluster.carac, 3
planfac, 14
plotFactoClass, 16
ward.cluster, 19

*Topic **multivariate**

centroids, 3
cluster.carac, 3
dudi.tex, 5
Fac.Num, 7
FactoClass, 7
FactoClass.tex, 10
kmeansW, 12
list.to.data, 13
planfac, 14
plotFactoClass, 16
stableclus, 17
ward.cluster, 19

analysis.clus (*FactoClass*), 7

Bogota, 1
BreedsDogs, 2

centroids, 3
cluster.carac, 3
ColorAdjective, 5

dudi.tex, 5

Fac.Num, 7
FactoClass, 7, 10, 11, 16, 17
FactoClass.tex, 9, 10

kmeansW, 12

latex (*dudi.tex*), 5
latexDF (*FactoClass.tex*), 10
list.to.data, 13

planfac, 14
plotFactoClass, 9, 16
print.FactoClass (*FactoClass*), 7
print.FactoClass.tex
(*FactoClass.tex*), 10

roundDF (*FactoClass.tex*), 10

stableclus, 17
sutil.grid (*planfac*), 14

Vietnam, 18

ward.cluster, 19