

Package ‘nlrx’

March 28, 2019

Type Package

Title Setup, Run and Analyze 'NetLogo' Model Simulations from 'R' via 'XML'

Version 0.2.0

Maintainer Jan Salecker <jsaleck@gwdg.de>

Description The purpose of this package is to provide tools to setup, run and analyze 'NetLogo' (<<https://ccl.northwestern.edu/netlogo/>>) model simulations in 'R'. 'nlrx' experiments use a similar structure as 'NetLogos' Behavior Space experiments. However, 'nlrx' offers more flexibility and additional tools for running and analyzing complex simulation designs and sensitivity analyses. The user defines all information that is needed in an intuitive framework, using class objects. Experiments are submitted from 'R' to 'NetLogo' via 'XML' files that are dynamically written, based on specifications defined by the user. By nesting model calls in future environments, large simulation design with many runs can be executed in parallel. This also enables simulating 'NetLogo' experiments on remote HPC machines. In order to use this package, 'Java' and 'NetLogo' (>= 5.3.1) need to be available on the executing system.

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

URL <https://github.com/nldoc/nlrx/>

BugReports <https://github.com/nldoc/nlrx/issues/>

Imports XML, lhs, sensitivity, dplyr, readr, purrr, furr, magrittr, stats, utils, GenSA, genalg, raster, rstudioapi, sf, tidyr, methods, tibble, igraph, stringr

Depends R (>= 3.3)

Suggests testthat, knitr, rmarkdown, covr

VignetteBuilder knitr

SystemRequirements 'NetLogo' (>= 5.3.1), 'Java' (JDK 1.8)

NeedsCompilation no

Author Jan Salecker [aut, cre] (<<https://orcid.org/0000-0002-9000-4229>>),
 Marco Sciaini [aut] (<<https://orcid.org/0000-0002-3042-5435>>),
 Marina Papadopoulou [rev] (Marina reviewed the package for ropensci,
 see <<https://github.com/ropensci/software-review/issues/262>>)

Repository CRAN

Date/Publication 2019-03-28 14:20:03 UTC

R topics documented:

nrx-package	3
analyze_nl	5
download_netlogo	7
eval_variables_constants	8
experiment	9
export_nl	13
getexp	14
getnl	15
getsim	15
import_nl	16
nl	17
nldoc	18
nldoc_network	19
nl_distinct	20
nl_eFast	21
nl_ff	21
nl_lhs	22
nl_morris	22
nl_simple	23
nl_sobol	23
nl_sobol2007	24
nl_soboljansen	24
nl_spatial	25
nl_to_graph	25
nl_to_points	27
nl_to_raster	28
report_model_parameters	28
run_nl_all	29
run_nl_dyn	30
run_nl_one	32
setexp<-	33
setnl<-	34
setsim<-	34
simdesign	35
simdesign_distinct	38
simdesign_eFast	39
simdesign_ff	40

simdesign_GenAlg	41
simdesign_GenSA	42
simdesign_lhs	43
simdesign_morris	44
simdesign_simple	45
simdesign_sobol	46
simdesign_sobol2007	47
simdesign_soboljansen	48
unnest_simoutput	49
write_simoutput	50

Index	51
--------------	-----------

nlrx-package	<i>nlrx: A package for running NetLogo simulations from R.</i>
--------------	--

Description

The nlrx package provides tools to setup NetLogo simulations in R. It uses a similar structure as NetLogos Behavior Space but offers more flexibility and additional tools for running sensitivity analyses.

Details

Get started:

General information that is needed to run NetLogo simulations remotely, such as path to the NetLogo installation folder is stored within a `nl` class object. Nested within this `nl` class are the classes `experiment` and `simdesign`. The `experiment` class stores all experiment specifications. After attaching a valid experiment, a `simdesign` class object can be attached to the `nl` class object, by using one of the `simdesign` helper functions. These helper functions create different parameter input matrices from the experiment variable definitions that can then be executed by the `run_nl_one()` and `run_nl_all()` functions. The nested design allows to store everything related to the experiment within one R object. Additionally, different `simdesign` helper functions can be applied to the same `nl` object in order to repeat the same experiment with different parameter exploration methods (`simdesigns`).

Step by step application example

The "Wolf Sheep Predation" model from the NetLogo models library is used to present a basic example on how to setup and run NetLogo model simulations from R.

Step 1: Create a `nl` object:

The `nl` object holds all information on the NetLogo version, a path to the NetLogo directory with the defined version, a path to the model file, and the desired memory for the java virtual machine. Depending on the operation system, paths to NetLogo and the model need to be adjusted.

```
library(nlrx)
# Windows default NetLogo installation path (adjust to your needs!):
netlogopath <- file.path("C:/Program Files/NetLogo 6.0.3")
```

```

modelpath <- file.path(netlogopath, "app/models/Sample Models/Biology/Wolf Sheep Predation.nlogo")
outpath <- file.path("C:/out")
# Unix default NetLogo installation path (adjust to your needs!):
netlogopath <- file.path("/home/NetLogo 6.0.3")
modelpath <- file.path(netlogopath, "app/models/Sample Models/Biology/Wolf Sheep Predation.nlogo")
outpath <- file.path("/home/out")
nl <- nl(nlversion = "6.0.3",
        nlpath = netlogopath,
        modelpath = modelpath,
        jvmmem = 1024)

```

Step 2: Attach an experiment

The experiment object is organized in a similar fashion as NetLogo Behavior Space experiments. It contains all information that is needed to generate a simulation parameter matrix and to execute the NetLogo simulations. Details on the specific slots of the experiment class can be found in the package documentation (`?experiment`) and the "Advanced configuration" vignette.

```

nl@experiment <- experiment(expname="wolf-sheep",
                           outpath=outpath,
                           repetition=1,
                           tickmetrics="true",
                           idsetup="setup",
                           idgo="go",
                           runtime=50,
                           evalticks=seq(40,50),
                           metrics=c("count sheep", "count wolves", "count patches with [pcolor = green]"),
                           variables = list('initial-number-sheep' = list(min=50, max=150, qfun="qunif"),
                                             'initial-number-wolves' = list(min=50, max=150, qfun="qunif")),
                           constants = list("model-version" = "\"sheep-wolves-grass\"",
                                             "grass-regrowth-time" = 30,
                                             "sheep-gain-from-food" = 4,
                                             "wolf-gain-from-food" = 20,
                                             "sheep-reproduce" = 4,
                                             "wolf-reproduce" = 5,
                                             "show-energy?" = "false"))

```

Step 3: Attach a simulation design

While the experiment defines the variables and specifications of the model, the simulation design creates a parameter input table based on these model specifications and the chosen simulation design method. `nlrx` provides a bunch of different simulation designs, such as full-factorial, latin-hypercube, sobol, morris and eFast (see "Simdesign Examples" vignette for more information on simdesigns). All simdesign helper functions need a properly defined `nl` object with a valid experiment design. Each simdesign helper also allows to define a number of random seeds that are randomly generated and can be used to execute repeated simulations of the same parameter matrix with different random-seeds (see "Advanced configuration" vignette for more information on random-seed and repetition management). A simulation design is attached to a `nl` object by using one of the simdesign helper functions:

```
nl@simdesign <- simdesign_lhs(nl=nl,
```

```
samples=100,  
nseeds=3,  
precision=3)
```

Step 4: Run simulations

All information that is needed to run the simulations is now stored within the `nl` object. The `run_nl_one()` function allows to run one specific simulation from the `siminput` parameter table. The `run_nl_all()` function runs a loop over all `simseeds` and rows of the parameter input table `siminput`. The loops are constructed in a way that allows easy parallelisation, either locally or on remote HPC machines (see "Advanced configuration" vignette for more information on parallelisation).

```
results <- run_nl_all(nl = nl)
```

Step 5: Attach results to `nl` and run analysis

`nrx` provides method specific analysis functions for each simulation design. Depending on the chosen design, the function reports a tibble with aggregated results or sensitivity indices. In order to run the `analyze_nl()` function, the simulation output has to be attached to the `nl` object first. After attaching the simulation results, these can also be written to the defined `outpath` of the experiment object.

```
# Attach results to nl object:  
setsim(nl, "simoutput") <- results  
# Write output to outpath of experiment within nl  
write_simoutput(nl)  
# Do further analysis:  
analyze_nl(nl)
```

Author(s)

Jan Salecker <jsaleck@gwdg.de>

See Also

Useful links:

- <https://github.com/nldoc/nlrx/>
- Report bugs at <https://github.com/nldoc/nlrx/issues/>

analyze_nl

Analyze NetLogo simulation output

Description

Analyze NetLogo simulation output

Usage

```
analyze_nl(nl, metrics = getexp(nl, "metrics"),
           funs = dplyr::funs(mean))
```

Arguments

nl	nl object
metrics	vector of strings defining metric columns for evaluation. Defaults to metrics of the experiment within the nl object
funs	dplyr::funs list with the summary metrics one wants to have for the sensitivity results

Details

The `analyze_nl` function runs basic analyses on NetLogo simulation output. In order to execute this function, simulation output needs to be attached to the `simdesign` first with `setsim(nl, "output") <- results`.

`analyze_nl` calls different post-processing analysis functions, depending on the specified method in the `simdesign` object of the `nl` object.

The following simdesign are currently supported:[simdesign_ff](#)

Calls `analyze_ff`. The function calculates aggregated output metrics by dropping random seeds and aggregating values with the provided functions.

[simdesign_lhs](#)

Calls `analyze_lhs`. The function calculates aggregated output metrics by dropping random seeds and aggregating values with the provided functions.

[simdesign_sobol](#)

Calls `analyze_sobol`. The function calculates sobol sensitivity indices from the output results using the `sensitivity` package.

[simdesign_sobol2007](#)

Calls `analyze_sobol2007`. The function calculates sobol sensitivity indices from the output results using the `sensitivity` package.

[simdesign_soboljansen](#)

Calls `analyze_soboljansen`. The function calculates sobol sensitivity indices from the output results using the `sensitivity` package.

[simdesign_morris](#)

Calls `analyze_morris`. The function calculates morris sensitivity indices from the output results using the `sensitivity` package.

[simdesign_eFast](#)

Calls `analyze_eFast`. The function calculates eFast sensitivity indices from the output results using the `sensitivity` package.

For the following simdesign no postprocessing analysis function has been implemented yet:

[simdesign_simple](#), [simdesign_distinct](#), [simdesign_GenSA](#), [simdesign_GenAlg](#)

Value

analysis summary tibble

Examples

```
# Load nl object including output data from testdata
nl <- nl_sobol

# Define aggregation measurements:
myfuns <- dplyr::funs(mean, sd, min, max)

# Calculate sensitivity indices:
analyze_nl(nl, funs = myfuns)
```

download_netlogo	<i>Download NetLogo</i>
------------------	-------------------------

Description

Auxiliary function to download NetLogo

Usage

```
download_netlogo(to, version, extract = FALSE)
```

Arguments

to	Path to folder where the downloaded file is saved.
version	Character string naming which NetLogo Version to download (see Details)
extract	TRUE/FALSE, if TRUE downloaded archive is extracted to subfolder of to (only unix)

Details

Supported Versions for Download and Usage (parameter version):

- "6.0.4" = NetLogo Version 6.0.4
- "6.0.3" = NetLogo Version 6.0.3
- "6.0.2" = NetLogo Version 6.0.2
- "6.0.1" = NetLogo Version 6.0.1
- "6.0" = NetLogo Version 6.0
- "5.3.1" = NetLogo Version 5.3.1

Examples

```
dlpath <- tempdir() # adjust path to your needs
download_netlogo(dlpath, "6.0.3")
```

eval_variables_constants

Evaluate variable validity

Description

Evaluate variables and constants defined in experiment

Usage

```
eval_variables_constants(nl)
```

Arguments

nl nl object

Details

This function checks if the variables and constants that are defined in the experiment are valid. It loads the model code of the NetLogo model and checks if these variables and constants really exist. In case of nonvalid entries, the function throws an error message, indicating which variables and constants are not valid. Please note, that this function might fail if the supported modelpath does not point to an existing nlogo file. This might for example happen, if the modelpath is set up for a remote cluster execution.

Examples

```
## Not run:
nl <- nl_lhs
eval_variables_constants(nl)

## End(Not run)
```

 experiment

Construct a new experiment object

Description

Construct a new experiment object

Usage

```
experiment(expname = "defaultexp", outputpath = NA_character_,
  repetition = 1, tickmetrics = "true", idsetup = "setup",
  idgo = "go", idfinal = NA_character_, idrunnum = NA_character_,
  runtime = 1, evalticks = NA_integer_, stopcond = NA_character_,
  metrics = c("count turtles"), metrics.turtles = list(),
  metrics.patches = NA_character_, metrics.links = list(),
  variables = list(), constants = list(), ...)
```

Arguments

expname	A character string defining the name of the experiment
outputpath	Path to a directory where experiment output will be stored
repetition	A number which gives the number of repetitions for each row of the simulation design input tibble
tickmetrics	Character string "true" runs defined metrics on each simulation tick. "false" runs metrics only after simulation is finished
idsetup	character string or vector of character strings, defining the name of the NetLogo setup procedure
idgo	character string or vector of character strings, defining the name of the NetLogo go procedure
idfinal	character string or vector of character strings, defining the name of NetLogo procedures that should be run after the last tick
idrunnum	character string, defining the name of a NetLogo global that should be used to parse the current siminputrow during model executions which can then be used for self-written output.
runtime	number of model ticks that should be run for each simulation
evalticks	vector of tick numbers defining when measurements are taken. NA_integer_ to measure each tick
stopcond	a NetLogo reporter that reports TRUE/FALSE. If it reports TRUE the current simulation run is stopped (e.g. "not any? turtles")
metrics	vector of strings defining valid NetLogo reporters that are taken as output measurements (e.g. c("count turtles", "count patches"))

<code>metrics.turtles</code>	a list with named vectors of strings defining valid turtles-own variables that are taken as output measurements (e.g. <code>list("turtles" = c("who", "pxcor", "pycor", "color"))</code>)
<code>metrics.patches</code>	vector of strings defining valid patches-own variables that are taken as output measurements (e.g. <code>c("pxcor", "pycor", "pcolor")</code>)
<code>metrics.links</code>	a list with named vectors of strings defining valid links-own variables that are taken as output measurements (e.g. <code>list("links" = c("end1", "end2"))</code>)
<code>variables</code>	a nested list of variables that are changed within a simulation design. The name of each sublist item has to be a valid global of the defined NetLogo model. Depending on the desired <code>simdesign</code> each list item consist of a vector of values, a min value, a max value, a step value and a <code>qfun</code> (e.g. <code>list("paramA" = list(values=c(0, 0.5, 1), min=0, max=1, step=0.1, qfun="qunif"))</code>)
<code>constants</code>	a list of constants that are kept constant within a simulation design. The name of each list item has to be a valid global of the defined NetLogo model (e.g. <code>list("pNUM" = 12, "pLOGIC"="TRUE", "pSTRING"="default")</code>)
<code>...</code>	<code>...</code>

Details

The `experiment` class stores all information related to the NetLogo simulation experiment. The class holds all information that is typically entered into NetLogo Behavior Space experiments. When setting up an experiment, it is usually attached to an already defined `nl` object (see examples). After attaching an experiment, different `simdesign` helper functions can be used to attach a `simdesign` to the `nl` object `simdesign`. The `simdesign` helper functions use the variable definitions from the experiment within the `nl` object to generate a parameter tibble for simulations.

The following class slots are obligatory to run an experiment:

repetition

In cases, where the random seed is controlled by `nrx simdesigns`, `repetition` should be set to one as random seeds would not differ between simulations. In cases, where the random seed is set within the NetLogo model, `repetition` can be increased to repeat the same parameterisation with different random seeds.

tickmetrics

If `"true"`, the defined output reporters are collected on each simulation tick that is defined in `evalticks`. If `"false"` measurements are taken only on the last tick.

idsetup, idgo

These two class slots accept strings, or vectors of strings, defining NetLogo model procedures that should be executed for model setup (`idsetup`) and model execution (`idgo`).

runtime

Defines the maximum number of simulation ticks that are executed. Use 0 or `NA_integer_` to execute simulations without predefined number of ticks. Warning: This is only recommended in combination with a stop condition (see slot `stopcond`), or NetLogo models with a built-in stop condition. Otherwise, simulations might get stuck in endless loops.

Depending on the simdesign, the following slots may be obligatory:*metrics*

A vector of valid netlogo reporters that defines which measurements are taken. The optimization simdesigns need at least one defined metrics reporter for fitness calculation of the optimization algorithm.

constants, variables

These slots accept lists with NetLogo parameters that should be varied within a simdesign (variables) or should be kept constant (constants) for each simulation. Any NetLogo parameter that is not entered in at least one of these two lists will be set up as constant with the default value from the NetLogo interface. It is not possible to enter a NetLogo parameter in both lists (a warning message will appear when a simdesign is attached to such an experiment). All simdesigns except [simdesign_simple](#) need defined variables for setting up a parameter matrix. Variables can be defined as distinct values, value distributions or range with increment. The information that is needed, depends on the chosen simdesign (details on variable definition requirements can be found in the helpfiles of each simdesign helper function).

All remaining slots are optional:*expname*

A character string defining the name of the experiment, useful for documentation purposes.

outpath

A valid path to an existing directory. The directory is used by the [write_simoutput](#) function to store attached simulation results to disk in csv format.

idfinal

A character string or vector of strings defining NetLogo procedures that are executed at the end of each simulation (e.g. cleanup or self-written output procedures).

idrunnum

This slot can be used to transfer the current nlr experiment name, random seed and runnumber (siminputrow) to NetLogo. To use this functionality, a string input field widget needs to be created on the GUI of your NetLogo model. The name of this widget can be entered into the "idrunnum" field of the experiment. During simulations, the value of this widget is automatically updated with a generated string that contains the current nlr experiment name, random seed and siminputrow ("expname_seed_siminputrow"). For self-written output In NetLogo, we suggest to include this global variable which allows referencing the self-written output files to the collected output of the nlr simulations in R.

evalticks

Only applied if tickmetrics = TRUE. Evalticks may contain a vector of integers, defining the ticks for which the defined metrics will be measured. Set evalticks to NA_integer_ to measure on every tick.

stopcond

The stopcond slot can be used to define a stop condition by providing a string with valid NetLogo code that reports either true or false. Each simulation will be stopped automatically, once the reporter reports true.

metrics.patches

The `metrics.patches` slot accepts a vector of valid patches-own variables of the NetLogo model. These patch variables are measured in addition to the defined metrics. Results of these metrics will be nested inside the output results tibble of the simulations. Please note that NetLogo models may contain a huge number of patches and output measurements of agent variables on each tick may need a lot of resources.

metrics.turtles

The `metrics.turtles` slot accepts a list with named vectors of valid turtle breed metrics. Each name of a vector in this list defines a specified breed of the NetLogo model, whereas the vector defines the variables that are measured for this breed. For example `metrics.turtles = list("sheep"=c("color"), "wolves"=c("who"))` - would measure the color of each sheep and the who number of each wolf agent. To measure <turtles-own> variables for all turtles, use `"turtles" = c(...)`. Be aware, that NetLogo will produce runtime errors if you measure <breed-own> variables for agents that do not belong to this breed. Please note that NetLogo models may contain a huge number of turtles and output measurements of agent variables on each tick may need a lot of resources.

metrics.links

The `metrics.links` slot accepts a list with named vectors of valid link breed metrics. Each name of a vector in this list defines a specified link breed of the NetLogo model, whereas the vector defines the variables that are measured for this link breed. For example `metrics.links = list("linktype-a"=c("end1"), "linktype-b"=c("end2"))` - would measure the start agent of each linktype-a link and the end agent of each linktype-b link. To measure <links-own> variables for all links, use `"links" = c(...)`. Be aware, that NetLogo will produce runtime errors if you measure <link-breed-own> variables for agents that do not belong to this breed. Please note that NetLogo models may contain a huge number of turtles and output measurements of agent variables on each tick may need a lot of resources.

Value

experiment S4 class object

Examples

```
# To attach an experiment, a nl object needs to be created first (see ?nl).
# For this example, we load a nl object from test data.
```

```
# Example for Wolf Sheep Predation model from NetLogo models library:
```

```
nl <- nl_simple
nl@experiment <- experiment(expname="wolf-sheep",
  outpath="C:/out/",
  repetition=1,
  tickmetrics="true",
  idsetup="setup",
  idgo="go",
  idfinal=NA_character_,
  idrunnum=NA_character_,
  runtime=50,
  evalticks=seq(40,50),
  stopcond="not any? turtles",
  metrics=c("count sheep",
```

```

        "count wolves",
        "count patches with [pcolor = green]"),
metrics.turtles=list("turtles" = c("who",
        "pxcor",
        "pycor",
        "color")),
metrics.patches=c("pxcor", "pycor", "pcolor"),
variables = list('initial-number-sheep' =
list(min=50, max=150, step=10, qfun="qunif"),
        'initial-number-wolves' =
list(min=50, max=150, step=10, qfun="qunif")),
constants = list("model-version" =
        "\"sheep-wolves-grass\"",
        "grass-regrowth-time" = 30,
        "sheep-gain-from-food" = 4,
        "wolf-gain-from-food" = 20,
        "sheep-reproduce" = 4,
        "wolf-reproduce" = 5,
        "show-energy?" = "false")

```

export_nl

Export NetLogo Experiment

Description

Export NetLogo Experiment as zip file

Usage

```
export_nl(nl, path = dirname(getnl(nl, "modelpath")), tarfile)
```

Arguments

nl	nl object
path	Path to folder that contains files to run NetLogo experiment
tarfile	Path to folder where the experiments gets stored as zip file

Details

Exports your folder that contains data and scripts for NetLogo + nlr analyses as a zip file. Furthermore, export_nl takes your nl object and saves it in the zipped folder. This enables other person to run the same experiment as you.

Value

The status value returned by the external command, invisibly.

Examples

```
# Load nl object from testdata:
nl <- nl_lhs
path <- getwd() # adjust path to your needs, path should point to a directory with model data
outfile <- tempfile(fileext = ".zip") # adjust file path to your needs
export_nl(nl, path = path, tarfile = outfile)
```

getexp

Getter function to get a variable of an experiment object

Description

Getter function to get a variable of an experiment object

Usage

```
getexp(nl, var)
```

Arguments

nl	nl object
var	valid experiment variable string

Examples

```
# Example for Wolf Sheep Predation model from NetLogo models library:
nl <- nl(nlversion = "6.0.3",
nlpath = "/home/user/NetLogo 6.0.3/",
modelpath = "/home/user/NetLogo 6.0.3/app/models/Sample Models/Biology/Wolf Sheep Predation.nlogo",
jvmmem = 1024)

# Set experiment name
setexp(nl, "expname") <- "experimentName"

# Get experiment name
getexp(nl, "experiment")
```

getnl *Getter function to get a variable of a nl object*

Description

Getter function to get a variable of a nl object

Usage

```
getnl(nl, var)
```

Arguments

nl	nl object
var	valid nl variable string

Examples

```
# Example for Wolf Sheep Predation model from NetLogo models library:
nl <- nl(nlversion = "6.0.3",
nlpath = "/home/user/NetLogo 6.0.3/",
modelpath = "/home/user/NetLogo 6.0.3/app/models/Sample Models/Biology/Wolf Sheep Predation.nlogo",
jvmmem = 1024)

# get NetLogo version
getnl(nl, "nlversion")
```

getsim *Getter function to get a variable of a simdesign object*

Description

Getter function to get a variable of a simdesign object

Usage

```
getsim(nl, var)
```

Arguments

nl	nl object
var	valid simdesign variable string

Examples

```
# Example for Wolf Sheep Predation model from NetLogo models library:
nl <- nl(nlversion = "6.0.3",
nlpath = "/home/user/NetLogo 6.0.3/",
modelpath = "/home/user/NetLogo 6.0.3/app/models/Sample Models/Biology/Wolf Sheep Predation.nlogo",
jvmem = 1024)

# Set simulation seeds
setsim(nl, "simseeds") <- c(123, 456, 789)

# Set simulation seeds
getsim(nl, "simseeds")
```

import_nl

Import NetLogo Experiment

Description

Import NetLogo Experiment from export_nl

Usage

```
import_nl(tarfile, targetdir, new_session = FALSE)
```

Arguments

tarfile	Path to tarfile that contains files to run NetLogo experiment
targetdir	Path to folder where the experiments gets extracted
new_session	If TRUE, opens a new RStudio Session with an Rproj

Details

Imports NetLogo experiments that were saved with export_nl. If the folder comes with an .Rproj file (which is recommended because relative paths enhance the reproducibility of your analysis), import_nl opens this project and loads the nl object in your R environment.

Value

The status value returned by the external command, invisibly.

Examples

```
## Not run:

infile <- "/home/user/test.zip"
targetdirectory <- "/home/user/test"
import_nl(infile, targetdirectory)

## End(Not run)
```

nl *Construct a new nl object*

Description

Construct a new nl object

Usage

```
nl(nlversion = "6.0.2", nlpath = character(),
  modelpath = character(), jvmmem = 1024,
  experiment = methods::new("experiment"),
  simdesign = methods::new("simdesign"), ...)
```

Arguments

nlversion	A character string defining the NetLogo version that is used
nlpath	Path to the NetLogo main directory matching the defined version
modelpath	Path to the NetLogo model file (*.nlogo) that is used for simulations
jvmmem	Java virtual machine memory capacity in megabytes
experiment	Holds a experiment S4 class object
simdesign	Holds a simdesign S4 class object
...	...

Details

nl objects are the main class objects used in the nlr package. These objects store all information that is needed to run NetLogo simulations. nl objects are initialized with basic information on Netlogo and the model.

After setting up the nl object, an experiment needs to be attached [experiment](#). The experiment class stores all information related to the NetLogo simulation experiment, such as runtime, variables, constants, measurements, and more.

After attaching an experiment, different simdesign helper functions can be used to attach a simdesign to the nl object [simdesign](#). The simdesign helper functions use the variable definitions from the experiment within the nl object to generate a parameter tibble for simulations.

Value

nl S4 class object

Examples

```
# Example for Wolf Sheep Predation model from NetLogo models library:
# Windows default NetLogo installation path (adjust to your needs!):
netlogopath <- file.path("C:/Program Files/NetLogo 6.0.3")
modelpath <- file.path(netlogopath, "app/models/Sample Models/Biology/Wolf Sheep Predation.nlogo")
outpath <- file.path("C:/out")
# Unix default NetLogo installation path (adjust to your needs!):
netlogopath <- file.path("/home/NetLogo 6.0.3")
modelpath <- file.path(netlogopath, "app/models/Sample Models/Biology/Wolf Sheep Predation.nlogo")
outpath <- file.path("/home/out")

nl <- nl(nlversion = "6.0.3",
        nlpath = netlogopath,
        modelpath = modelpath,
        jvmem = 1024)
```

nldoc

Create NetLogo documentation

Description

Create NetLogo documentation

Usage

```
nldoc(modelfiles, outpath, infotab = TRUE, gui = TRUE, bs = TRUE,
      output_format = "html", number_sections = TRUE, theme = "journal",
      date = today(), toc = TRUE)
```

Arguments

modelfiles	vector of filepaths to model files
outpath	Path to folder where rendered documentation should be created
infotab	TRUE/FALSE, if TRUE infotab section will be included in the documentation
gui	TRUE/FALSE, if TRUE a table with GUI elements from the model will be included in the documentation
bs	TRUE/FALSE, if TRUE a table with behavior space experiments will be included in the documentation
output_format	either "html", "pdf" or "docx"
number_sections	TRUE/FALSE, if TRUE sections in the documentation will be numbered
theme	markdown theme, supported themes are "journal", "cerulean", "flatly", "readable", "spacelab", "united", "cosmo"
date	date that is printed in the documentation header
toc	TRUE/FALSE, if TRUE the documentation contains a table of contents - only for html and pdf output format

Details

nldoc reads model code from the provided model files. The code is then split into several groups (code, gui, behavior space). The procedures then finds noxygen commands within the NetLogo model code. For a complete list of noxygen commands type ?nldoc These commands are translated into a markdown documentation file. If needed, tables of gui elements and behavior space experiments are added to the markdown file. Finally, the document is rendered in the specified format.

Examples

```
# List model files (.nls subfiles are also supported)
modelfiles <- c("https://raw.githubusercontent.com/nldoc/nldoc_pg/master/WSP.nlogo",
               "https://raw.githubusercontent.com/nldoc/nldoc_pg/master/WSP.nls")

# Define output directory:
outdir <- tempdir() # adjust path to your needs

# Create documentation:
nldoc(modelfiles = modelfiles,
      infotab=TRUE,
      gui=TRUE,
      bs=TRUE,
      outputpath = outdir,
      output_format = "html",
      number_sections = TRUE,
      theme = "cosmo",
      date = date(),
      toc = TRUE)
```

nldoc_network

Create NetLogo procedure network

Description

Create NetLogo procedure network

Usage

```
nldoc_network(modelfiles)
```

Arguments

modelfiles vector of filepaths to model files

Details

Reads model code from the provided model files. The procedure identifies NetLogo procedures and searches for procedure calls within the code. From this data, an igraph network is created and returned. This network can be used to plot the model procedure network and identify model components.

Value

network of model procedures (igraph)

Examples

```
# List model files (.nls subfiles are also supported)
modelfiles <- c("https://raw.githubusercontent.com/nldoc/nldoc_pg/master/WSP.nlogo",
               "https://raw.githubusercontent.com/nldoc/nldoc_pg/master/WSP.nls")

# Determine the function network:
nw <- nldoc_network(modelfiles)

# Determine communities within the network and plot using Igraph package:
library(igraph)
com <- walktrap_community(nw)
V(nw)$community <- com$membership
rain <- rainbow(14, alpha=.5)
V(nw)$color <- rain[V(nw)$community]

plot(nw,
     edge.arrow.size=.2,
     vertex.label.color="black",
     vertex.label.dist=1,
     vertex.size=5,
     edge.curved=0,
     vertex.label.cex=.5,
     layout=layout_with_fr(nw, niter = 2000))

# Interactive plot using igraph::tkplot
tkplot(nw, layout=layout_with_fr(nw, niter = 2000))
```

nl_distinct

Wolf Sheep model sample data: simdesign distinct

Description

The dataset contains a complete nl object. The nl object has been used to setup and run a distinct simulation design. It also contains the model outputs within the simdesign object.

Usage

nl_distinct

Format

nl object with defined experiment, simdesign and model output

nl_eFast*Wolf Sheep model sample data: simdesign eFast*

Description

The dataset contains a complete nl object. The nl object has been used to setup and run an eFast simulation design. It also contains the model outputs within the simdesign object. Further analysis output can be derived by submitting the dataset to analyze_nl().

Usage

nl_eFast

Format

nl object with defined experiment, simdesign and model output

nl_ff*Wolf Sheep model sample data: simdesign ff*

Description

The dataset contains a complete nl object. The nl object has been used to setup and run a full-factorial simulation design. It also contains the model outputs within the simdesign object. Further analysis output can be derived by submitting the dataset to analyze_nl().

Usage

nl_ff

Format

nl object with defined experiment, simdesign and model output

nl_lhs	<i>Wolf Sheep model sample data: simdesign lhs</i>
--------	--

Description

The dataset contains a complete nl object. The nl object has been used to setup and run a latin hypercube simulation design. It also contains the model outputs within the simdesign object. Further analysis output can be derived by submitting the dataset to `analyze_nl()`.

Usage

nl_lhs

Format

nl object with defined experiment, simdesign and model output

nl_morris	<i>Wolf Sheep model sample data: simdesign morris</i>
-----------	---

Description

The dataset contains a complete nl object. The nl object has been used to setup and run a morris simulation design. It also contains the model outputs within the simdesign object. Further analysis output can be derived by submitting the dataset to `analyze_nl()`.

Usage

nl_morris

Format

nl object with defined experiment, simdesign and model output

nl_simple	<i>Wolf Sheep model sample data: simdesign simple</i>
-----------	---

Description

The dataset contains a complete nl object. The nl object has been used to setup and run a simple simulation design. It also contains the model outputs within the simdesign object.

Usage

nl_simple

Format

nl object with defined experiment, simdesign and model output

nl_sobol	<i>Wolf Sheep model sample data: simdesign sobol</i>
----------	--

Description

The dataset contains a complete nl object. The nl object has been used to setup and run a sobol simulation design. It also contains the model outputs within the simdesign object. Further analysis output can be derived by submitting the dataset to `analyze_nl()`.

Usage

nl_sobol

Format

nl object with defined experiment, simdesign and model output

`nl_sobol2007`*Wolf Sheep model sample data: simdesign sobol2007*

Description

The dataset contains a complete nl object. The nl object has been used to setup and run a sobol2007 simulation design. It also contains the model outputs within the simdesign object. Further analysis output can be derived by submitting the dataset to `analyze_nl()`.

Usage`nl_sobol2007`**Format**

nl object with defined experiment, simdesign and model output

`nl_soboljansen`*Wolf Sheep model sample data: simdesign soboljansen*

Description

The dataset contains a complete nl object. The nl object has been used to setup and run a soboljansen simulation design. It also contains the model outputs within the simdesign object. Further analysis output can be derived by submitting the dataset to `analyze_nl()`.

Usage`nl_soboljansen`**Format**

nl object with defined experiment, simdesign and model output

nl_spatial

Wolf Sheep model sample data: spatial

Description

The dataset contains a complete nl object. The nl object has been used to setup and run a simple simulation design. For these simulations, spatial agent output has been collected. metrics.turtles was set up to measure turtle coordinates. metrics.patches was set up to measure colors of cells. It also contains the model outputs within the simdesign object.

Usage

```
nl_spatial
```

Format

nl object with defined experiment, simdesign and model output

nl_to_graph

Generate igraph objects from measured turtles and links metrics

Description

Generate igraph objects from measured turtles and links metrics

Usage

```
nl_to_graph(nl)
```

Arguments

nl nl object

Generate igraph objects from measured turtles and links metrics. Output has to be attached to the simdesign first with `simoutput(nl) <- results` I graph objects are created automatically for each combination of random-seed, siminputrow and step. An additional column with igraph objects is attached to the original output results tibble of the nl object. In order to generate igraph objects some metrics are mandatory: The metrics.turtles slot of the experiment must contain "who" numbers (see example experiment). Additional turtle metrics will be stored as properties of the igraph vertices. The metrics.links slot of the experiment must contain "who" numbers of link end1 and end2 (see example experiment). Additional link metrics will be stored as properties of the igraph edges.

Examples

```

## Not run:
## Example running the Giant Component model from the NetLogo models library:
library(nlrx)
library(igraph)
# Windows default NetLogo installation path (adjust to your needs!):
netlogopath <- file.path("C:/Program Files/NetLogo 6.0.4")
modelpath <- file.path(netlogopath, "app/models/Sample Models/Networks/Giant Component.nlogo")
outpath <- file.path("C:/out")
# Unix default NetLogo installation path (adjust to your needs!):
netlogopath <- file.path("/home/NetLogo 6.0.4")
modelpath <- file.path(netlogopath, "app/models/Sample Models/Networks/Giant Component.nlogo")
outpath <- file.path("/home/out")

nl <- nl(nlversion = "6.0.4",
        nlpath = netlogopath,
        modelpath = modelpath,
        jvmmem = 1024)

nl@experiment <- experiment(expname="networks",
                            outpath=outpath,
                            repetition=1,
                            tickmetrics="false",
                            idsetup="setup",
                            idgo="go",
                            runtime=50,
                            metrics.turtles = list("turtles" = c("who", "color")),
                            metrics.links = list("links" = c("[who] of end1", "[who] of end2")),
                            constants = list("num-nodes" = 80,
                                              "layout?" = "true"))

nl@simdesign <- simdesign_simple(nl, 1)
nl@simdesign@simoutput <- run_nl_all(nl)
nl.graph <- nl_to_graph(nl)

## Extract graph of tick 1:
nl.graph.i <- nl.graph$spatial.links[[1]]
## Set vertex colors by measured color variable:
vcols <- c("7" = "grey", "15" = "red")
V(nl.graph.i)$color <- vcols[as.character(V(nl.graph.i)$color)]
## Set edge colors by measured link breed:
ecols <- c("links" = "black")
E(nl.graph.i)$color <- ecols[E(nl.graph.i)$breed]

## Plot:
plot.igraph(nl.graph.i, vertex.size=8, vertex.label=NA, edge.arrow.size=0.2)

## End(Not run)

```

nl_to_points	<i>Get spatial data from metrics.turtles output</i>
--------------	---

Description

Turn turtle metrics from NetLogo in spatial data objects

Usage

```
nl_to_points(nl, coords)
```

Arguments

nl	nl object
coords	nl object

Details

Converts measured metrics.turtles into spatial sf point objects. In order to so, a pair of turtle coordinates needs to be measured. Any additional metrics will be stored as properties of the spatial points. Because turtle coordinates in NetLogo can be measured in two formats, pxcor/pycor or xcor/ycor coordinates, the type of coordinate used for transformation to spatial objects need to be defined, using the parameter coords: "px" for pxcor/pycor coordinates, "x" for xcor/ycor coordinates.

In order to use this function, simulation results need to be attached to the nl object first.

Value

tibble with spatial data objects

Examples

```
# Load nl object (with spatial output data already attached) from test data:  
nl <- nl_spatial  
  
# Convert turtle metrics (pxcor/pycor) to spatial point objects:  
results.sf <- nl_to_points(nl, coords="px")
```

`nl_to_raster`*Get spatial data from metrics.patches output*

Description

Turn patch metrics from NetLogo in spatial data objects

Usage

```
nl_to_raster(nl)
```

Arguments

`nl` `nl` object

Details

Converts measured metrics.patches into spatial raster objects. In order to so, a patch coordinates needs to be measured (pxcor/pycor). For each additional patch metric, a raster will be created using the measured coordinates as x and y and the additional metric as z dimension. In case of multiple measured metrics, a raster stack with one raster for each metric will be reported.

In order to use this function, simulation results need to be attached to the `nl` object first.

Value

tibble with spatial data objects

Examples

```
# Load nl object (with spatial output data already attached) from test data:  
nl <- nl_spatial  
  
# Convert patch metrics to spatial raster objects:  
results.raster <- nl_to_raster(nl)
```

`report_model_parameters`*Report globals from a NetLogo model that is defined within a nl object*

Description

Report globals from a NetLogo model that is defined within a `nl` object

Usage

```
report_model_parameters(nl)
```

Arguments

nl nl object with a defined modelpath that points to a NetLogo model (*.nlogo)

Details

The function reads the NetLogo model file that is defined within the nl object and reports all global parameters that are defined as widget elements on the GUI of the NetLogo model. Only globals that are found by this function are valid globals that can be entered into the variables or constants vector of an experiment object.

Examples

```
## Not run:
nl <- nl_lhs
report_model_parameters(nl)

## End(Not run)
```

run_nl_all

Execute all NetLogo simulations from a nl object

Description

Execute all NetLogo simulations from a nl object with a defined experiment and simdesign

Usage

```
run_nl_all(nl, split = 1, cleanup.csv = TRUE, cleanup.xml = TRUE,
  cleanup.bat = TRUE, silent = TRUE)
```

Arguments

nl	nl object
split	number of parts the job should be split into
cleanup.csv	TRUE/FALSE, if TRUE temporary created csv output files will be deleted after gathering results.
cleanup.xml	TRUE/FALSE, if TRUE temporary created xml output files will be deleted after gathering results.
cleanup.bat	TRUE/FALSE, if TRUE temporary created bat/sh output files will be deleted after gathering results.
silent	TRUE/FALSE, if FALSE prints the current seed and siminputrow after successful execution of a simulation (only for sequential execution).

Details

run_nl_all executes all simulations of the specified NetLogo model within the provided nl object. The function loops over all random seeds and all rows of the siminput table of the simdesign of nl. The loops are created by calling `future_map_dfr`, which allows running the function either locally or on remote HPC machines. The logical cleanup variables can be set to FALSE to preserve temporary generated output files (e.g. for debugging). `cleanup.csv` deletes/keeps the temporary generated model output files from each run. `cleanup.xml` deletes/keeps the temporary generated experiment xml files from each run. `cleanup.bat` deletes/keeps the temporary generated batch/sh commandline files from each run.

When using run_nl_all in a parallelized environment (e.g. by setting up a future plan using the future package), the outer loop of this function (random seeds) creates jobs that are distributed to available cores of the current machine. The inner loop (siminputrows) distributes simulation tasks to these cores. However, it might be advantageous to split up large jobs into smaller jobs for example to reduce the total runtime of each job. This can be done using the split parameter. If split is > 1 the siminput matrix is split into smaller parts. Jobs are created for each combination of part and random seed. If the split parameter is set such that the siminput matrix can not be splitted into equal parts, the procedure will stop and throw an error message.

Value

tibble with simulation output results

Examples

```
## Not run:

# Load nl object from test data:
nl <- nl_lhs

# Execute all simulations from an nl object with properly attached simdesign.
results <- run_nl_all(nl)

# Run in parallel on local machine:
library(future)
plan(multisession)
results %<-% run_nl_all(nl)

## End(Not run)
```

run_nl_dyn

Execute NetLogo simulation without pregenerated parametersets

Description

Execute NetLogo simulation from a nl object with a defined experiment and simdesign but no pregenerated input parametersets

Usage

```
run_nl_dyn(nl, seed, cleanup.csv = TRUE, cleanup.xml = TRUE,
           cleanup.bat = TRUE, silent = TRUE)
```

Arguments

nl	nl object
seed	a random seed for the NetLogo simulation
cleanup.csv	TRUE/FALSE, if TRUE temporary created csv output files will be deleted after gathering results.
cleanup.xml	TRUE/FALSE, if TRUE temporary created xml output files will be deleted after gathering results.
cleanup.bat	TRUE/FALSE, if TRUE temporary created bat/sh output files will be deleted after gathering results.
silent	TRUE/FALSE, if FALSE prints the current seed and siminputrow after successful execution of a simulation (only for sequential execution).

Details

run_nl_dyn can be used for simdesigns where no predefined parametersets exist. This is the case for dynamic designs, such as Simulated Annealing and Genetic Algorithms, where parametersets are dynamically generated, based on the output of previous simulations. The logical cleanup variables can be set to FALSE to preserve temporary generated output files (e.g. for debugging). cleanup.csv deletes/keeps the temporary generated model output files from each run. cleanup.xml deletes/keeps the temporary generated experiment xml files from each run. cleanup.bat deletes/keeps the temporary generated batch/sh commandline files from each run.

Value

simulation output results can be tibble, list, ...

Examples

```
## Not run:

# Load nl object form test data:
nl <- nl_lhs

# Add genalg simdesign:
nl@simdesign <- simdesign_GenAlg(nl=nl,
                              popSize = 200,
                              iters = 100,
                              evalcrit = 1,
                              nseeds = 1)

# Run simulations:
results <- run_nl_dyn(nl)
```

```
## End(Not run)
```

run_nl_one	<i>Execute one NetLogo simulation from a nl object</i>
------------	--

Description

Execute one NetLogo simulation from a nl object with a defined experiment and simdesign

Usage

```
run_nl_one(nl, seed, siminputrow, cleanup.csv = TRUE,
           cleanup.xml = TRUE, cleanup.bat = TRUE, silent = TRUE)
```

Arguments

nl	nl object
seed	a random seed for the NetLogo simulation
siminputrow	rownumber of the input tibble within the attached simdesign object that should be executed
cleanup.csv	TRUE/FALSE, if TRUE temporary created csv output files will be deleted after gathering results.
cleanup.xml	TRUE/FALSE, if TRUE temporary created xml output files will be deleted after gathering results.
cleanup.bat	TRUE/FALSE, if TRUE temporary created bat/sh output files will be deleted after gathering results.
silent	TRUE/FALSE, if FALSE prints the current seed and siminputrow after successful execution of a simulation (only for sequential execution).

Details

run_nl_one executes one simulation of the specified NetLogo model within the provided nl object. The random seed is set within the NetLogo model to control stochasticity. The siminputrow number defines which row of the input data tibble within the simdesign object of the provided nl object is executed. The logical cleanup variables can be set to FALSE to preserve temporary generated output files (e.g. for debugging). cleanup.csv deletes/keeps the temporary generated model output files from each run. cleanup.xml deletes/keeps the temporary generated experiment xml files from each run. cleanup.bat deletes/keeps the temporary generated batch/sh commandline files from each run.

This function can be used to run single simulations of a NetLogo model.

Value

tibble with simulation output results

Examples

```
## Not run:

# Load nl object from test data:
nl <- nl_lhs

# Run one simulation:
results <- run_nl_one(nl = nl,
                     seed = getsim(nl, "simseeds")[1],
                     siminputrow = 1)

## End(Not run)
```

setexp<-

Setter function to set a variable of an experiment object

Description

Setter function to set a variable of an experiment object

Usage

```
setexp(nl, var) <- value
```

Arguments

nl	nl object
var	valid experiment variable string
value	valid value for the specified variable

Examples

```
# Example for Wolf Sheep Predation model from NetLogo models library:
nl <- nl(nlversion = "6.0.3",
        nlpath = "/home/user/NetLogo 6.0.3/",
        modelpath = "/home/user/NetLogo 6.0.3/app/models/Sample Models/Biology/Wolf Sheep Predation.nlogo",
        jvmmem = 1024)

# Set experiment name
setexp(nl, "expname") <- "experimentName"
```

setnl<- *Setter function to set a variable of a nl object*

Description

Setter function to set a variable of a nl object

Usage

```
setnl(nl, var) <- value
```

Arguments

nl	nl object
var	valid nl variable string
value	valid value for the specified variable

Examples

```
# Example for Wolf Sheep Predation model from NetLogo models library:
nl <- nl(
  nlpath = "/home/user/NetLogo 6.0.3/",
  modelpath = "/home/user/NetLogo 6.0.3/app/models/Sample Models/Biology/Wolf Sheep Predation.nlogo",
  jvmmem = 1024)

# set NetLogo version
setnl(nl, "nlversion") <- "6.0.3"
```

setsim<- *Setter function to set a variable of a simdesign object*

Description

Setter function to set a variable of a simdesign object

Usage

```
setsim(nl, var) <- value
```

Arguments

nl	nl object
var	valid simdesign variable string
value	valid value for the specified variable

Examples

```
# Example for Wolf Sheep Predation model from NetLogo models library:
nl <- nl(nlversion = "6.0.3",
nlpath = "/home/user/NetLogo 6.0.3/",
modelpath = "/home/user/NetLogo 6.0.3/app/models/Sample Models/Biology/Wolf Sheep Predation.nlogo",
jvmem = 1024)

# Set simulation seeds
setsim(nl, "simseeds") <- c(123, 456, 789)
```

simdesign	<i>Construct a new simdesign object</i>
-----------	---

Description

Construct a new simdesign object

Usage

```
simdesign(simmethod = character(), siminput = tibble::tibble(),
simobject = list(), simseeds = NA_integer_,
simoutput = tibble::tibble(), ...)
```

Arguments

simmethod	character string defining the method of the simulation design
siminput	tibble providing input parameterisations for the NetLogo model (cols=parameter, rows=runs)
simobject	used for some methods to store additional information (sobol, morris, eFast)
simseeds	a vector or model random seeds
simoutput	tibble containing model results
...	...

Details

The simulation design class holds information on the input parameter design of model simulations. It also stores information that is needed to run method specific analysis functions. The simseeds can be used to run all model simulations that are defined within the siminput tibble several times with changing random-seeds. While it is possible to add simdesign directly with this function, we suggest to use our simdesign_helper functions. A simulation design can be attached to a nl object by using one of these simdesign_helper functions on an already defined nl object with a valid [experiment](#). All simdesign helpers use the defined constants and variables of the experiment to create the siminput tibble. NetLogo parameters that are not defined in constants or variables will be set with their default value from the NetLogo interface.

Currently, following simdesign_helper functions are provided:

[simdesign_simple](#)

The simple simdesign only uses defined constants and reports a parameter matrix with only one parameterization. To setup a simple simdesign, no variables have to be defined.

[simdesign_distinct](#)

The distinct simdesign can be used to run distinct parameter combinations. To setup a distinct simdesign, vectors of values need to be defined for each variable. These vectors must have the same number of elements across all variables. The first simulation run consist of all 1st elements of these variable vectors; the second run uses all 2nd values, and so on.

[simdesign_ff](#)

The full factorial simdesign creates a full-factorial parameter matrix with all possible combinations of parameter values. To setup a full-factorial simdesign, vectors of values need to be defined for each variable. Alternatively, a sequence can be defined by setting min, max and step. However, if both (values and min, max, step) are defined, the values vector is prioritized.

[simdesign_lhs](#)

The latin hypercube simdesign creates a Latin Hypercube sampling parameter matrix. The method can be used to generate a near-random sample of parameter values from the defined parameter distributions. More Details on Latin Hypercube Sampling can be found in [McKay 1979](#). nlr uses the [lhs](#) package to generate the Latin Hypercube parameter matrix. To setup a latin hypercube sampling simdesign, variable distributions need to be defined (min, max, qfun).

Sensitivity Analyses: [simdesign_sobol](#), [simdesign_sobol2007](#), [simdesign_soboljansen](#), [simdesign_morris](#), [simdesign_eFast](#)

Sensitivity analyses are useful to estimate the importance of model parameters and to scan the parameter space in an efficient way. nlr uses the [sensitivity](#) package to setup sensitivity analysis parameter matrices. All supported sensitivity analysis simdesigns can be used to calculate sensitivity indices for each parameter-output combination. These indices can be calculated by using the [analyze_nl](#) function after attaching the simulation results to the nl object. To setup sensitivity analysis simdesigns, variable distributions (min, max, qfun) need to be defined.

Optimization techniques: [simdesign_GenSA](#), [simdesign_GenAlg](#)

Optimization techniques are a powerful tool to search the parameter space for specific solutions. Both approaches try to minimize a specified model output reporter by systematically (genetic algorithm, utilizing the [genalg](#) package) or randomly (simulated annealing, utilizing the [genSA](#) package) changing the model parameters within the allowed ranges. To setup optimization simdesigns, variable ranges (min, max) need to be defined. Optimization simdesigns can only be executed using the [run_nl_dyn](#) function instead of [run_nl_all](#) or [run_nl_one](#).

Value

simdesign S4 class object

Examples

```
# To attach a simdesign, a nl object needs to be created first (see ?nl).
# For this example, we load nl objects from test data.

# Simdesign examples for Wolf Sheep Predation model from NetLogo models library:
```



```

nl@simdesign <- simdesign_eFast(nl=nl,
                             samples=100,
                             nseeds=3)

nl <- nl_lhs
nl@simdesign <- simdesign_GenAlg(nl=nl,
                              popSize = 200,
                              iters = 100,
                              evalcrit = 1,
                              elitism = NA,
                              mutationChance = NA,
                              nseeds = 1)

nl <- nl_lhs
nl@simdesign <- simdesign_GenSA(nl=nl,
                              par=NULL,
                              evalcrit=1,
                              control=list(max.time = 600),
                              nseeds=1)

```

simdesign_distinct *Add a distinct simdesign to a nl object*

Description

Add a distinct simdesign to a nl object

Usage

```
simdesign_distinct(nl, nseeds)
```

Arguments

nl	nl object with a defined experiment
nseeds	number of seeds for this simulation design

Details

This function creates a simdesign S4 class which can be added to a nl object. The distinct simdesign allows to create a parameter matrix with distinct parameterisations.

Variables in the experiment variable list need to provide a vector of distinct values (e.g. list(values=c(1,2,3,4)). All vectors of values must have the same length across variables.

The distinct simdesign then creates one simulation run for all first elements of these values vectors, one run for all second items, and so on. With this function, multiple distinct simulations can be run at once. Finally, the function reports a simdesign object.

Value

simdesign S4 class object

Examples

```
# To attach a simdesign, a nl object needs to be created first (see ?nl).
# For this example, we load a nl object from test data.

nl <- nl_distinct
nl@simdesign <- simdesign_distinct(nl = nl, nseeds = 3)
```

simdesign_eFast *Add an eFast simdesign to a nl object*

Description

Add an eFast simdesign to a nl object

Usage

```
simdesign_eFast(nl, samples, nseeds)
```

Arguments

nl	nl object with a defined experiment
samples	number of samples for the eFast sensitivity analysis
nseeds	number of seeds for this simulation design

Details

This function creates a simdesign S4 class which can be added to a nl object.

Variables in the experiment variable list need to provide a numeric distribution with min, max and qfun (e.g. list(min=1, max=4, qfun="qunif")).

The eFast simdesign uses the sensitivity package to set up a fast99 elementary effects sensitivity analysis, including a simobject of class fast99 and a input tibble for simulations. For details on method specific sensitivity analysis function parameters see ?fast99 Finally, the function reports a simdesign object.

Value

simdesign S4 class object

Examples

```
# To attach a simdesign, a nl object needs to be created first (see ?nl).
# For this example, we load a nl object from test data.

nl <- nl_eFast
nl@simdesign <- simdesign_eFast(nl=nl,
                             samples=100,
                             nseeds=1)
```

simdesign_ff

Add a full-factorial simdesign to a nl object

Description

Add a full-factorial simdesign to a nl object

Usage

```
simdesign_ff(nl, nseeds)
```

Arguments

nl	nl object with a defined experiment
nseeds	number of seeds for this simulation design

Details

This function creates a simdesign S4 class which can be added to a nl object.

Variables in the experiment variable list need to provide a vector of distinct values (e.g. list(values=c(1,2,3,4)). Or a sequence definition with min, max and step (e.g. list=(min=1, max=4, step=1)). If both (values and sequence) are defined, the full-factorial design gives priority to the values.

The full-factorial simdesign uses these defined parameter ranges within the nl object. A full-factorial matrix of all parameter combinations is created as input tibble for the simdesign. Finally, the function reports a simdesign object.

Value

simdesign S4 class object

Examples

```
# To attach a simdesign, a nl object needs to be created first (see ?nl).
# For this example, we load a nl object from test data.

nl <- nl_ff
nl@simdesign <- simdesign_ff(nl = nl, nseeds = 3)
```

<code>simdesign_GenAlg</code>	<i>Add a Genetic Algorithm simdesign to a nl object</i>
-------------------------------	---

Description

Add a Genetic Algorithm simdesign to a nl object

Usage

```
simdesign_GenAlg(nl, popSize = 200, iters = 100, evalcrit = 1,
  elitism = NA, mutationChance = NA, nseeds = 1)
```

Arguments

<code>nl</code>	nl object with a defined experiment
<code>popSize</code>	population Size parameter for genetic algorithm
<code>iters</code>	number of iterations for genetic algorithm function
<code>evalcrit</code>	position of evaluation criterion within defined NetLogo metrics of nl experiment
<code>elitism</code>	elitism rate of genetic algorithm function
<code>mutationChance</code>	mutation rate of genetic algorithm function
<code>nseeds</code>	number of seeds for this simulation design

Details

This function creates a simdesign S4 class which can be added to a nl object.

Variables in the experiment variable list need to provide a numeric distribution with min and max (e.g. `list(min=1, max=4)`).

The GenAlg simdesign generates a Genetic Algorithm experiment within the defined min and max parameter boundaries that are defined in the variables field of the experiment object within the nl object. The evalcrit reporter defines the evaluation criterion for the simulated annealing procedure. The reporter is defined within the experiment metrics vector. For the Genetic Algorithm function we only refer to the position of the reporter that we want to use for evaluation. The function uses the `genalg` package to set up a Genetic Algorithm function. For details on the `genalg` function parameters see `?genalg::rbga`. Finally, the function reports a simdesign object.

Genetic Algorithm simdesigns can only be executed using the `run_nl_dyn` function instead of `run_nl_all` or `run_nl_one`.

Value

simdesign S4 class object

Examples

```
# To attach a simdesign, a nl object needs to be created first (see ?nl).
# For this example, we load a nl object from test data.
```

```
nl <- nl_lhs
nl@simdesign <- simdesign_GenAlg(nl=nl,
                              nseeds=1)
```

simdesign_GenSA	<i>Add a Simulated Annealing simdesign to a nl object</i>
-----------------	---

Description

Add a Simulated Annealing simdesign to a nl object

Usage

```
simdesign_GenSA(nl, par = NULL, evalcrit = 1, control = list(),
               nseeds = 1)
```

Arguments

nl	nl object with a defined experiment
par	optional vector of start values for each parameter defined in variables of experiment
evalcrit	position of evaluation criterion within defined NetLogo metrics of nl experiment
control	list with further arguments passed to the GenSA function (see ?GenSA for details)
nseeds	number of seeds for this simulation design

Details

This function creates a simdesign S4 class which can be added to a nl object.

Variables in the experiment variable list need to provide a numeric distribution with min and max (e.g. list(min=1, max=4)).

The GenSA simdesign generates a simulated Annealing experiment within the defined min and max parameter boundaries that are defined in the variables field of the experiment object within the nl object. The evalcrit reporter defines the evaluation criterion for the simulated annealing procedure.

The reporter is defined within the experiment metrics vector. For the simulated annealing function we only refer to the position of the reporter that we want to use for evaluation. The function uses the GenSA package to set up a Simulated Annealing function. For details on the GenSA function parameters see `?GenSA`. Finally, the function reports a simdesign object.

Simulated Annealing simdesigns can only be executed using the `run_nl_dyn` function instead of `run_nl_all` or `run_nl_one`.

Value

simdesign S4 class object

Examples

```
# To attach a simdesign, a nl object needs to be created first (see ?nl).
# For this example, we load a nl object from test data.
```

```
nl <- nl_lhs
nl@simdesign <- simdesign_GenSA(nl=nl,
                             par=NULL,
                             evalcrit=1,
                             control=list(max.time = 600),
                             nseeds=1)
```

<code>simdesign_lhs</code>	<i>Add a latin-hypercube simdesign to a nl object</i>
----------------------------	---

Description

Add a latin-hypercube simdesign to a nl object

Usage

```
simdesign_lhs(nl, samples, nseeds, precision)
```

Arguments

<code>nl</code>	nl object with a defined experiment
<code>samples</code>	number of samples for the latin hypercube
<code>nseeds</code>	number of seeds for this simulation design
<code>precision</code>	number of digits for the decimal fraction of parameter values

Details

This function creates a simdesign S4 class which can be added to a nl object.

Variables in the experiment variable list need to provide a numeric distribution with min, max and qfun (e.g. list(min=1, max=4, qfun="qunif").

The latin hypercube simdesign creates a parameter matrix based on these defined distributions. Finally, the function reports a simdesign object.

Value

simdesign S4 class object

Examples

```
# To attach a simdesign, a nl object needs to be created first (see ?nl).
# For this example, we load a nl object from test data.
```

```
nl <- nl_lhs
nl@simdesign <- simdesign_lhs(nl=nl,
                             samples=100,
                             nseeds=3,
                             precision=3)
```

simdesign_morris *Add a morris elementary effects simdesign to a nl object*

Description

Add a morris elementary effects simdesign to a nl object

Usage

```
simdesign_morris(nl, morristype, morrislevels, morrisr, morrisgridjump,
                nseeds)
```

Arguments

nl	nl object with a defined experiment
morristype	morris design type
morrislevels	number of parameter levels
morrisr	morris r value
morrisgridjump	morris grid jump value
nseeds	number of seeds for this simulation design

Details

This function creates a simdesign S4 class which can be added to a nl object.

Variables in the experiment variable list need to provide a numeric distribution with min, max and qfun (e.g. list(min=1, max=4, qfun="qunif").

The morris simdesign uses the sensitivity package to set up a morris elementary effects sensitivity analysis, including a simobject of class morris and a input tibble for simulations. For details on method specific sensitivity analysis function parameters see ?morris Finally, the function reports a simdesign object.

Value

simdesign S4 class object

Examples

```
# To attach a simdesign, a nl object needs to be created first (see ?nl).  
# For this example, we load a nl object from test data.
```

```
nl <- nl_morris  
nl@simdesign <- simdesign_morris(nl=nl,  
                               morristype="oat",  
                               morrislevels=4,  
                               morrisr=20,  
                               morrisgridjump=2,  
                               nseeds=3)
```

simdesign_simple	<i>Add a simple simdesign to a nl object</i>
------------------	--

Description

Add a simple simdesign to a nl object

Usage

```
simdesign_simple(nl, nseeds)
```

Arguments

nl	nl object with a defined experiment
nseeds	number of seeds for this simulation design

Details

This function creates a simdesign S4 class which can be added to a nl object. The simple simdesign only uses model parameters that are defined in the constants field of the experiment object within the nl object. Thus, the resulting input tibble of the simdesign has only one run with constant parameterisations. This can be useful to run one simulation with a specific parameterset. Finally, the function reports a simdesign object.

Value

simdesign S4 class object

Examples

```
# To attach a simdesign, a nl object needs to be created first (see ?nl).
# For this example, we load a nl object from test data.

nl <- nl_simple
nl@simdesign <- simdesign_simple(nl = nl, nseeds = 3)
```

simdesign_sobol	<i>Add a sobol simdesign to a nl object</i>
-----------------	---

Description

Add a sobol simdesign to a nl object

Usage

```
simdesign_sobol(nl, samples, sobolorder, sobolnboot, sobolconf, nseeds,
  precision)
```

Arguments

nl	nl object with a defined experiment
samples	number of samples for the sobol sensitivity analysis
sobolorder	order of interactions of the sobol sensitivity analysis
sobolnboot	number of bootstrap replicates of the sobol sensitivity analysis
sobolconf	the confidence level for bootstrap confidence intervals
nseeds	number of seeds for this simulation design
precision	number of digits for the decimal fraction of parameter values

Details

This function creates a simdesign S4 class which can be added to a nl object.

Variables in the experiment variable list need to provide a numeric distribution with min, max and qfun (e.g. list(min=1, max=4, qfun="qunif")).

The sobol simdesign uses the sensitivity package to set up a sobol sensitivity analysis, including a simobject of class sobol and a input tibble for simulations. For details on method specific sensitivity analysis function parameters see ?sobol Finally, the function reports a simdesign object.

Value

simdesign S4 class object

Examples

```
# To attach a simdesign, a nl object needs to be created first (see ?nl).
# For this example, we load a nl object from test data.
```

```
nl <- nl_sobol
nl@simdesign <- simdesign_sobol(nl=nl,
  samples=1000,
  sobolorder=2,
  sobolnboot=100,
  sobolconf=0.95,
  nseeds=3,
  precision=3)
```

simdesign_sobol2007 *Add a sobol2007 simdesign to a nl object*

Description

Add a sobol2007 simdesign to a nl object

Usage

```
simdesign_sobol2007(nl, samples, sobolnboot, sobolconf, nseeds, precision)
```

Arguments

nl	nl object with a defined experiment
samples	number of samples for the sobol sensitivity analysis
sobolnboot	number of bootstrap replicates of the sobol sensitivity analysis
sobolconf	the confidence level for bootstrap confidence intervals
nseeds	number of seeds for this simulation design
precision	number of digits for the decimal fraction of parameter values

Details

This function creates a simdesign S4 class which can be added to a nl object.

Variables in the experiment variable list need to provide a numeric distribution with min, max and qfun (e.g. list(min=1, max=4, qfun="qunif")).

The sobol2007 simdesign uses the sensitivity package to set up a sobol2007 sensitivity analysis, including a simobject of class sobol and a input tibble for simulations. For details on method specific sensitivity analysis function parameters see ?sobol2007 Finally, the function reports a simdesign object.

Value

simdesign S4 class object

Examples

```
# To attach a simdesign, a nl object needs to be created first (see ?nl).
# For this example, we load a nl object from test data.
```

```
nl <- nl_sobol2007
nl@simdesign <- simdesign_sobol2007(nl=nl,
  samples=1000,
  sobolnboot=100,
  sobolconf=0.95,
  nseeds=3,
  precision=3)
```

simdesign_soboljansen *Add a soboljansen simdesign to a nl object*

Description

Add a soboljansen simdesign to a nl object

Usage

```
simdesign_soboljansen(nl, samples, sobolnboot, sobolconf, nseeds,
  precision)
```

Arguments

nl	nl object with a defined experiment
samples	number of samples for the sobol sensitivity analysis
sobolnboot	number of bootstrap replicates of the sobol sensitivity analysis
sobolconf	the confidence level for bootstrap confidence intervals

nseeds number of seeds for this simulation design
 precision number of digits for the decimal fraction of parameter values

Details

This function creates a simdesign S4 class which can be added to a nl object.

Variables in the experiment variable list need to provide a numeric distribution with min, max and qfun (e.g. list(min=1, max=4, qfun="qunif").

The soboljansen simdesign uses the sensitivity package to set up a soboljansen sensitivity analysis, including a simobject of class sobol and a input tibble for simulations. For details on method specific sensitivity analysis function parameters see ?soboljansen Finally, the function reports a simdesign object.

Value

simdesign S4 class object

Examples

```
# To attach a simdesign, a nl object needs to be created first (see ?nl).
# For this example, we load a nl object from test data.
```

```
nl <- nl_soboljansen
nl@simdesign <- simdesign_soboljansen(nl=nl,
  samples=1000,
  sobolnboot=100,
  sobolconf=0.95,
  nseeds=3,
  precision=3)
```

unnest_simoutput *Get spatial data from metrics.turtles and metrics.patches output*

Description

Turn results from NetLogo in spatial data objects

Usage

```
unnest_simoutput(nl)
```

Arguments

nl nl object

Details

Unnests output from run_nl into long format.

Value

tibble with spatial data objects

Examples

```
# To unnest data a nl object containing spatial output data is needed.
# For this example, we load a nl object from test data.

nl <- nl_spatial
unnest_simoutput(nl)
```

write_simoutput	<i>Write attached NetLogo simulation output to file</i>
-----------------	---

Description

Write attached NetLogo simulation output to file

Usage

```
write_simoutput(nl, outpath = NA)
```

Arguments

nl	nl object
outpath	optional path to directory where output is written

Write NetLogo simulation output to a csv file in the directory outpath of the nl object Output has to be attached to the simdesign first with simoutput(nl) <- results The outpath argument can be optionally used to write output to a different directory than the defined outpath of the nl object.

Examples

```
# Load nl object including output data from testdata
nl <- nl_lhs

# Write output to outpath directory
write_simoutput(nl, outpath=tempdir())
```

Index

*Topic **datasets**

- nl_distinct, 20
- nl_eFast, 21
- nl_ff, 21
- nl_lhs, 22
- nl_morris, 22
- nl_simple, 23
- nl_sobol, 23
- nl_sobol2007, 24
- nl_soboljansen, 24
- nl_spatial, 25

*Topic **package**

- nlr-package, 3

- analyze_eFast, 6
- analyze_ff, 6
- analyze_lhs, 6
- analyze_morris, 6
- analyze_nl, 5, 36
- analyze_sobol, 6
- analyze_sobol2007, 6
- analyze_soboljansen, 6

- download_netlogo, 7

- eval_variables_constants, 8
- experiment, 9, 17, 35
- export_nl, 13

- future_map_dfr, 30

- getexp, 14
- getnl, 15
- getsim, 15

- import_nl, 16

- nl, 10, 17, 35
- nl_distinct, 20
- nl_eFast, 21
- nl_ff, 21

- nl_lhs, 22
- nl_morris, 22
- nl_simple, 23
- nl_sobol, 23
- nl_sobol2007, 24
- nl_soboljansen, 24
- nl_spatial, 25
- nl_to_graph, 25
- nl_to_points, 27
- nl_to_raster, 28
- nldoc, 18
- nldoc_network, 19
- nlr (nlr-package), 3
- nlr-package, 3

- report_model_parameters, 28
- run_nl_all, 29, 36, 41, 43
- run_nl_dyn, 30, 36, 41, 43
- run_nl_one, 32, 36, 41, 43

- sensitivity, 6
- setexp (setexp<-), 33
- setexp<-, 33
- setnl (setnl<-), 34
- setnl<-, 34
- setsim (setsim<-), 34
- setsim<-, 34
- simdesign, 10, 17, 35
- simdesign_distinct, 6, 36, 38
- simdesign_eFast, 6, 36, 39
- simdesign_ff, 6, 36, 40
- simdesign_GenAlg, 6, 36, 41
- simdesign_GenSA, 6, 36, 42
- simdesign_lhs, 6, 36, 43
- simdesign_morris, 6, 36, 44
- simdesign_simple, 6, 11, 36, 45
- simdesign_sobol, 6, 36, 46
- simdesign_sobol2007, 6, 36, 47
- simdesign_soboljansen, 6, 36, 48

`unnest_simoutput`, [49](#)

`write_simoutput`, [11](#), [50](#)