

Package ‘quantregRanger’

December 15, 2017

Type Package

Title Quantile Regression Forests for 'ranger'

Description This is the implementation of quantile regression forests for the fast random forest package 'ranger'.

URL <https://github.com/PhilippPro/quantregRanger>

BugReports <https://github.com/PhilippPro/quantregRanger/issues>

License GPL-3

Encoding UTF-8

Depends R (>= 3.0.2), stats

Imports Rcpp (>= 0.12.2), ranger

LinkingTo Rcpp

LazyData yes

ByteCompile yes

Version 1.0

Date 2017-12-15

RoxygenNote 6.0.1

Suggests testthat

NeedsCompilation yes

Author Philipp Probst [aut, cre]

Maintainer Philipp Probst <philipp_probst@gmx.de>

Repository CRAN

Date/Publication 2017-12-15 11:43:17 UTC

R topics documented:

predict.quantregRanger	2
quantregRanger	2

Index	4
--------------	----------

predict.quantregRanger

quantregRanger prediction

Description

Predicts quantiles for a quantile regression forest trained with quantregRanger.

Usage

```
## S3 method for class 'quantregRanger'
predict(object, data = NULL, quantiles = c(0.1,
  0.5, 0.9), all = TRUE, obs = 1, ...)
```

Arguments

object	quantregRanger object.
data	New test data of class data.frame
quantiles	Numeric vector of quantiles that should be estimated
all	A logical value. all=TRUE uses all observations for prediction. all=FALSE uses only a certain number of observations per node for prediction (set with argument obs). The default is all=TRUE
obs	An integer number. Determines the maximal number of observations per node
...	Currently ignored. to use for prediction. The input is ignored for all=TRUE. The default is obs=1

Value

A matrix. The first column contains the conditional quantile estimates for the first entry in the vector quantiles. The second column contains the estimates for the second entry of quantiles and so on.

quantregRanger

Quantile Regression with Ranger

Description

Creates a quantile regression forest like described in Meinshausen, 2006.

Usage

```
quantregRanger(formula = NULL, data = NULL, params.ranger = NULL)
```

Arguments

<code>formula</code>	Object of class <code>formula</code> or character describing the model to fit.
<code>data</code>	Training data of class <code>data.frame</code> , <code>matrix</code> or <code>gwaab.data</code> (GenABEL).
<code>params.ranger</code>	List of further parameters that should be passed to <code>ranger</code> . See ranger for possible parameters.

Author(s)

Philipp Probst

References

Meinshausen, Nicolai. "Quantile regression forests." *The Journal of Machine Learning Research* 7 (2006): 983-999.

See Also

[predict.quantregRanger](#)

Examples

```
y = rnorm(150)
x = cbind(y + rnorm(150), rnorm(150))
data = data.frame(x,y)
mod = quantregRanger(y ~ ., data = data, params.ranger = list(mtry = 2))
predict(mod, data = data[1:5, ], quantiles = c(0.1, 0.5, 0.9))
```

Index

`predict.quantregRanger`, [2](#), [3](#)

`quantregRanger`, [2](#)

`ranger`, [3](#)