

Package ‘tidyrules’

June 14, 2019

Type Package

Title Obtain Rules from Rule Based Models as Tidy Dataframe

Version 0.1.0

Maintainer Srikanth Komala Sheshachala <sri.teach@gmail.com>

Depends R (>= 3.6.0),

Imports tibble (>= 2.0.1), stringr (>= 1.3.1), magrittr (>= 1.5),
purrr (>= 0.3.2), assertthat (>= 0.2.0), partykit (>= 1.2.2),

Suggests AmesHousing (>= 0.0.3), dplyr (>= 0.8), C50 (>= 0.1.2),
Cubist (>= 0.2.2), rpart (>= 1.2.2), rpart.plot (>= 3.0.7),
rsample (>= 0.0.2), testthat (>= 2.0.1), MASS (>= 7.3.50),
mlbench (>= 2.1.1), knitr (>= 1.23), rmarkdown (>= 1.13),
pander (>= 0.6.3),

Description Utility to convert text based summary of rule based models to a tidy dataframe (where each row represents a rule) with related metrics such as support, confidence and lift. Rule based models from these packages are supported: 'C5.0', 'rpart' and 'Cubist'.

URL <https://github.com/talegari/tidyrules>

BugReports <https://github.com/talegari/tidyrules/issues>

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

VignetteBuilder knitr

NeedsCompilation no

Author Srikanth Komala Sheshachala [aut, cre],
Amith Kumar Ullur Raghavendra [aut]

Repository CRAN

Date/Publication 2019-06-14 10:40:03 UTC

R topics documented:

addBackquotes	2
package_tidyrules	3
positionSpaceOutsideSinglequotes	3
removeEmptyLines	4
strHead	4
strReplaceReduce	5
strSplitSingle	6
strTail	6
tidyRules	7
tidyRules.C5.0	8
tidyRules.cubist	8
tidyRules.rpart	9
varSpec	10

Index	12
--------------	-----------

addBackquotes	<i>Add backquotes</i>
---------------	-----------------------

Description

(vectorized) Add backquotes when a string has a space in it

Usage

```
addBackquotes(string)
```

Arguments

string character vector

Value

character vector

Examples

```
tidyrules:::addBackquotes(c("ab", "a b"))
```

package_tidyrules *About 'tidyrules' package*

Description

Obtain rules as tidy dataframes

Author(s)

Maintainer: Srikanth Komala Sheshachala <sri.teach@gmail.com>

Authors:

- Amith Kumar Ullur Raghavendra <amith54@gmail.com>

See Also

Useful links:

- <https://github.com/talegari/tidyrules>
- Report bugs at <https://github.com/talegari/tidyrules/issues>

positionSpaceOutsideSinglequotes
Position of space outside single quotes

Description

(vectorised) Detect the position of space in a string not within a pair of single quotes

Usage

```
positionSpaceOutsideSinglequotes(string)
```

Arguments

string A character vector

Value

A integer vector of positions

Examples

```
tidyrules:::positionSpaceOutsideSinglequotes(c("hello", "hel' 'o "))
```

removeEmptyLines *Remove empty lines*

Description

Remove empty strings from a character vector

Usage

```
removeEmptyLines(strings)
```

Arguments

strings A character vector

Value

A character vector

Examples

```
tidyrules:::removeEmptyLines(c("abc", "", "d"))
```

strHead *Vectorized semantic equivalent of 'head' for a string*

Description

Picks the substring starting from the first character

Usage

```
strHead(string, n)
```

Arguments

string string
n (integer) Number of characters

Details

'n' can be in the interval [-len + 1, len] (both ends inclusive)

Value

A string

Examples

```
tidyrules:::strHead(c("string", "string2"), 2)
tidyrules:::strHead(c("string", "string2"), -1)
```

strReplaceReduce	<i>Sequential string replace</i>
------------------	----------------------------------

Description

Sequential string replace via reduce

Usage

```
strReplaceReduce(string, pattern, replacement)
```

Arguments

string	string
pattern	pattern
replacement	replacement

Value

character vector

Examples

```
tidyrules:::strReplaceReduce("abcd", c("ab", "dc"), c("cd", "ab"))
```

strSplitSingle *String split a string*

Description

and return a character vector (not a list)

Usage

```
strSplitSingle(string, pattern)
```

Arguments

string	A string
pattern	Passed as-is to 'stringr::str_split'

Value

A character vector

Examples

```
tidyrules:::strSplitSingle("abc,d", ",")
```

strTail *Vectorized semantic equivalent of tail for a string*

Description

Picks the substring starting from the first character

Usage

```
strTail(string, n)
```

Arguments

string	string
n	(integer) Number of characters

Details

'n' can be in the interval [-len + 1, len] (both ends inclusive)

Value

A string

Examples

```
tidyrules:::strTail(c("string", "string2"), 2)
tidyrules:::strTail(c("string", "string2"), -1)
```

tidyRules	<i>Obtain rules as a tidy tibble</i>
-----------	--------------------------------------

Description

Each row corresponds to a rule. A rule can be copied into ‘dplyr::filter‘ to filter the observations corresponding to a rule

Usage

```
tidyRules(object, col_classes = NULL, ...)
```

Arguments

object	Fitted model object with rules
col_classes	Named list or a named character vector of column classes. Column names of the data used for modeling form the names and the respective classes for the value. One way of obtaining this is by running ‘lapply(data, class)’.
...	Other arguments (currently unused)

Details

tidyRule supports these rule based models: C5, Cubist and rpart.

Value

A tibble where each row corresponds to a rule

Author(s)

Srikanth KS, <sri.teach@gmail.com>

tidyRules.C5.0	<i>Obtain rules as a tidy tibble from a C5.0 model</i>
----------------	--

Description

Each row corresponds to a rule. A rule can be copied into ‘dplyr::filter’ to filter the observations corresponding to a rule

Usage

```
## S3 method for class 'C5.0'
tidyRules(object, ...)
```

Arguments

object	Fitted model object with rules
...	Other arguments (currently unused)

Value

A tibble where each row corresponds to a rule. The columns are: support, confidence, lift, lhs, rhs, n_conditions

Author(s)

Srikanth KS, <sri.teach@gmail.com>

Examples

```
data("attrition", package = "rsample")
attrition <- tibble::as_tibble(attrition)
c5_model <- C50::C5.0(Attrition ~., data = attrition, rules = TRUE)
summary(c5_model)
tidyRules(c5_model)
```

tidyRules.cubist	<i>Obtain rules as a tidy tibble from a cubist model</i>
------------------	--

Description

Each row corresponds to a rule. A rule can be copied into ‘dplyr::filter’ to filter the observations corresponding to a rule

Usage

```
## S3 method for class 'cubist'
tidyRules(object, ...)
```


Arguments

object	Fitted model object with rules
...	Other arguments (currently unused)

Details

When `col_classes` argument is missing, an educated guess is made about class by parsing the RHS of sub-rule. This might sometimes not lead to a parsable rule.

Value

A tibble where each row corresponds to a rule. The columns are: support, mean, min, max, error, lhs, rhs and committee

Author(s)

Srikanth KS, <sri.teach@gmail.com>

Examples

```
data("attrition", package = "rsample")
attrition <- tibble::as_tibble(attrition)
cols_att <- setdiff(colnames(attrition), c("MonthlyIncome", "Attrition"))

cb_att <-
  Cubist::cubist(x = attrition[, cols_att], y = attrition[["MonthlyIncome"]])
tr_att <- tidyRules(cb_att)
tr_att
```

tidyRules.rpart

Obtain rules as a tidy tibble from a rpart model

Description

Each row corresponds to a rule. A rule can be copied into `'dplyr::filter'` to filter the observations corresponding to a rule

Usage

```
## S3 method for class 'rpart'
tidyRules(object, ...)
```

Arguments

object	Fitted model object with rules
...	Other arguments (currently unused)

Details

NOTE: For rpart rules, one should build the model without **ordered factor** variable. We recommend you to convert **ordered factor** to **factor** or **integer** class.

Value

A tibble where each row corresponds to a rule. The columns are: support, confidence, lift, LHS, RHS

Author(s)

Amith Kumar U R, <amith54@gmail.com>

Examples

```
iris_rpart <- rpart::rpart(Species ~ ., data = iris)
tidyRules(iris_rpart)
```

varSpec

Get variable specification for a Cubist/C5 object

Description

Obtain variable names, type (numeric, ordered, factor) and levels as a tibble

Usage

```
varSpec(object)
```

Arguments

object Cubist/C5 object

Value

A tibble with three columns: variable(character), type(character) and levels(a list-column). For numeric variables, levels are set to NA.

Author(s)

Srikanth KS, <sri.teach@gmail.com>

Examples

```
data("attrition", package = "rsample")
attrition <- tibble::as_tibble(attrition)
cols_att <- setdiff(colnames(attrition), c("MonthlyIncome", "Attrition"))

cb_att <-
  Cubist::cubist(x = attrition[, cols_att], y = attrition[["MonthlyIncome"]])
varSpec(cb_att)
```

Index

`addBackquotes`, 2

`package_tidyrules`, 3

`package_tidyrules-package`
(`package_tidyrules`), 3

`positionSpaceOutsideSinglequotes`, 3

`removeEmptyLines`, 4

`strHead`, 4

`strReplaceReduce`, 5

`strSplitSingle`, 6

`strTail`, 6

`tidyRules`, 7

`tidyrules` (`package_tidyrules`), 3

`tidyrules-package` (`package_tidyrules`), 3

`tidyRules.C5.0`, 8

`tidyRules.cubist`, 8

`tidyRules.rpart`, 9

`varSpec`, 10